

BULLED S 30W floodlight with PIR, 2400lm, IP44, 4000K, aluminium + glass

Adviti

Marka: **ADVITI** | Symbol: **AD-NL-6137BLR4** | Ean: **5908254817335**



PRODUCT DESCRIPTION

BULLED S floodlight is suitable for use both - at home and in industrial areas (e.g. garages, halls). Its light source in form of SMD LEDs, emits light in a natural white color suitable for lighting rooms with a lot of glazing and steel. Neutral light is also used to illuminate facades or gardens, so BULLED floodlight will be perfect to provide light to outdoor spaces like: car parks, entrances to property, building walls, or to illuminate advertisements, etc. IP44 ingress protection rating ensures its sufficient resistance to dust, dirt and water, and the use of aluminum and glass for the production guarantees resistance to all harsh weather conditions. The

device has a built-in PIR sensor that reacts to motion and allows to set the lighting time according to your preferences. The maximum detection range is 8 meters, and the time setting varies from 10 +/- seconds to 10 +/- minutes. The product comes with a connection block, instead of a power cord, which ensures a neat and hermetic connection with the power supply.

TECHNICAL DATA

General information:

Luminous flux:	2400 lm
Rated power:	30 W
Light source:	LED SMD
Degree of protection (IP):	44
Colour temperature:	4000
Nominal voltage:	230V~, 50Hz
Colour:	black
Solar panel:	No
Dimensions - depth:	75 mm
Dimensions - width:	155 mm
Dimensions - height:	158 mm
Colour rendering index CRI:	>80
Detection angle:	120°
Control of the motion sensor:	Yes
Type of sensor:	PIR
Detection range:	4-8 m
Adjustable daylight sensor (LUX):	Yes
Daylight sensor adjustment range (LUX):	<10 LUX~2000
Adjustable time setting (TIME):	Yes
Lighting time adjustment range (TIME):	10S±3S~10Min±3
Adjustment of motion detection range (SENS):	Yes



