

ALLED set of 2 x 100W floodlights with tripod and 2m cable

AdvitiMarka: **ADVITI** | Symbol: **AD-NL-6592** | Ean: **5908254847028**

PRODUCT DESCRIPTION

The set of 2 ALLED 2x100W floodlights with a tripod and a wire is a device suitable for use at homes and indoor spaces (garages, halls, warehouses) as well as outdoors serving as illumination of parking lots, gardens, properties or advertisement banners. The set is equipped with two 100W floodlights with LED SMD diodes providing strong and smooth illumination. LED SMD technology makes them more energy-saving as well as more durable and resistant to mechanical damages in comparison with traditional bulbs. The light with pleasant neutral temperature of 4000K does not strain eyes, and the luminous flux of 8000lm and wide beam

angle of $>80^\circ$ guarantee strong light and well-lit space. The LED SMD source of light is not replaceable.

The aluminium construction with high ingress protection rate of IP65 is resistant to harsh weather conditions, and the impact protection rate of IK08 ensures resistance to damages.

The telescopic tripod facilitates smooth height adjustment up to 160cm, which enables to position the light in any direction. The installation of the set is extremely easy, as the floodlight's power cord (2m long) is already connected with a plug. One needs simply to fix the devices to the tripod. The wire's cross section measures 3x1mm².

The colour of the housing is black and yellow. The dimensions of the floodlights measure 272x225x30 mm.

TECHNICAL DATA

General information:

Nominal voltage [V]:	230
Lamp type:	LED, niewymienne
Suitable for lamp power [W]:	2x100
Rated luminous flux according to IEC 62722-2-1 [lm]:	2x8000
Suitable for number of lamps:	2
With light source:	tak
Colour temperature [K]:	4000
Max. system power [W]:	200
Beam angle:	Wiązka bardzo szeroka $> 80^\circ$
Rated life time L70/B50 at 25 °C [h]:	35000
Colour rendering index CRI:	80-89
Energy efficiency class of the built-in lamp:	E
Colour of light:	Neutralny biały
Degree of protection (IP):	IP65
Impact strength:	IK08
Protection class:	I
Material housing:	Aluminium

Colour housing:	Czarny/Żółty
Voltage type:	AC
With connection cord and plug:	tak
The length of the power cord [m]:	2
Conductor cross section[mm ²]:	3x1
Width [mm]:	850
Height/depth [mm]:	1600
Length [mm]:	850
Other features:	Regulowany statyw



