

LAVILED set of 2 x 50 W floodlights with tripod, cord and bag

AdvitiMarka: **ADVITI** | Symbol: **AD-NL-6616** | Ean: **5908254852114**

PRODUCT DESCRIPTION

The LAVILED floodlight set is suitable when powerful and uniform lighting is required, such as in a garage, on a construction site, in a workshop, or during renovation and installation work. The set includes two 50 W LED floodlights, an adjustable tripod, a power cable, a Y-type cable connector, and a transport bag for easy carrying between workstations.

The floodlights generate a total luminous flux of 9000 lm with a neutral color temperature of 4000 K, providing

precise illumination and clear visibility of details. A high color rendering index (CRI > 90) allows accurate assessment of true surface colors, which is essential for painting, finishing work, or interior photography. The no-flicker effects ensures visual comfort even during long working hours, reducing eye strain and eliminating issues typical of lower-quality floodlights, such as visible light pulsation in photos and video recordings.

The telescopic tripod can be adjusted to a height of up to 156 cm, and the lightweight floodlight bar can be rotated to direct the light exactly where it is needed. The power cable has a total length of 3 meters (0.5 m from the floodlights to the connector and 2.5 m from the connector to the plug), providing flexibility when positioning the set at the work site.

The floodlights feature aluminum housing with an IP65 protection level, making them resistant to dust and moisture and suitable for outdoor use, even in rainy conditions. An IK07 mechanical impact rating enhances safety when working in more demanding environments. The integrated LED light sources offer a service life of up to 30,000 hours, while the wide beam angle ensures illumination of large areas without the need for frequent repositioning of the tripod.

The Y-type connector allows quick connection of the floodlights to a single power cable and simplifies replacement of individual components of the set.

The transport bag allows all components to be packed into a single unit, making it easy to carry the lamps between job sites or store the equipment neatly in a warehouse.

TECHNICAL DATA

General information:

Nominal voltage [V]:	230
Lamp type:	LED, niewymienne
Suitable for lamp power [W]:	2x50
Rated luminous flux according to IEC 62722-2-1 [lm]:	2x4500
Suitable for number of lamps:	2
With light source:	tak
Colour temperature [K]:	4000
Beam angle:	Wiązka bardzo szeroka > 80°
Rated life time L70/B50 at 25 °C [h]:	30000
Colour rendering index CRI:	90-100
Energy efficiency class of the built-in lamp:	F

Colour of light:	Neutralny biały
Degree of protection (IP):	IP65
Impact strength:	IK07
Protection class:	I
Material housing:	Aluminium
Colour housing:	Czarny/Pomarańczowy
Voltage type:	AC
The length of the power cord [m]:	3
Conductor cross section[mm ²]:	3x1
Width [mm]:	88
Height/depth [mm]:	156
Length [mm]:	88
Other features:	Regulowany statyw, torba transportowa





