







## EURUS LED 20W downlight, white flush-mounted, round, 1600lm, 3000K, built-in LED driver

Marka: ADVITI | Symbol: AD-OD-6053WLX3 | Ean: 5908254822995

**Adviti** 



## PRODUCT DESCRIPTION

The recessed luminaire from the EURUS series emits warm light of 3000K. The downlight is equipped with a non-replaceable 20W LED light source with a lifespan of up to 25,000 hours. Round light fixture with a power of 1600lm is designed for mounting in ceilings. The outer diameter of 240mm and a durable construction with an IP20 degree of protection, make EURUS a universal solution for lighting in residential, office or exhibition rooms. The luminaire is made of solid quality and easy-to-clean plastic in white.









## **TECHNICAL DATA**

## General information:

| The minimum distance from the illuminated object: | 0,5 m                |
|---|----------------------|
| Outer diameter:                                   | 240 mm               |
| Nominal voltage:                                  | 230 V                |
| Lamp type:  | LED, not replaceable |
| Suitable for lamp power:                          | 20 W                 |
| Rated luminous flux according to IEC 62722-2-1:   | 1600 lm              |
| With light source:                                | Yes                  |
| Colour temperature:                               | 3000 K               |
| Max. power:                                       | 20W                  |
| Beam angle:                                       | 360°                 |
| Rated life time L70/B50 at 25 °C:                 | 25000 h              |
| Colour rendering index CRI:                       | >80                  |
| Material housing:                                 | Plastic              |
| Energy efficiency class of the built-in lamp:     | F                    |
| Degree of protection (IP):                        | IP20                 |
| Colour of light:                                  | Warm                 |
| Flickering value Pst LM:                          | 0.1                  |
| Stroboscope effect value SVM:                     | 0.1                  |
| Protection class against electric shock:          | II                   |
| Suitable for ceiling mounting:                    | Yes                  |
| Suitable for built-in mounting:                   | Yes                  |
| Suitable for surface mounting:                    | No                   |
| Colour housing:                                   | White                |
| Height/depth:                                     | 32 mm                |
| Built-in height/depth:                            | 32 mm                |
| Built-in diameter:                                | 225 mm               |