

HEMERA LED Downlight 2-in-1, 7 W, 650 lm, 3000/4000/6500 K, black

Adviti

 Marka: **ADVITI** | Symbol: **AD-OD-6630BL/CCT** | Ean: **5908254852503**


PRODUCT DESCRIPTION

Choose the adjustable HEMERA LED lamp! The 650 lm beam at 7 W power perfectly highlights a selected part of the room or illuminates a usable area.

The fixture allows you to change the colour temperature of the light. With one setting you may choose warm 3000 K, neutral 4000 K or cool 6500 K light, depending on the function the lighting is to perform.

The flexible design allows you to adjust the direction of light. You can direct it towards a wall, alcove, picture or part of a countertop. The high colour rendering index RA 95 guarantees faithful colour reproduction, making the lighting ideal for places where perfect presentation is important – such as shops or exhibition halls. At home, it provides comfortable conditions for work and rest.

This model is suitable for surface and flush mounting, both on ceilings and walls. It works with compatible LED dimmers.

The black housing suits modern and loft interiors where light is to be an element of the composition.

TECHNICAL DATA

General information:

Nominal voltage [V]:	230
Lamp type:	LED, niewymienne
Suitable for lamp power [W]:	7
Rated luminous flux according to IEC 62722-2-1 [lm]:	650
Suitable for number of lamps:	1
With light source:	tak
Colour temperature [K]:	3000/4000/6500
Beam angle:	Wiązka szerokokątna 41-80°
Rated life time L70/B50 at 25 °C [h]:	25000
Colour rendering index CRI:	90-100
Light source with the ability to change the light color:	tak
Energy efficiency class of the built-in lamp:	F
Colour of light:	Wielobarwny
Degree of protection (IP):	IP20
Impact strength:	IK06
Protection class:	II
Suitable for wall mounting:	tak
Suitable for ceiling mounting:	tak
Suitable for built-in mounting:	tak

Suitable for surface mounting:	tak
Material housing:	Tworzywo sztuczne
Colour housing:	Czarny
Material cover:	Tworzywo sztuczne strukturyzowane
Height/depth [mm]:	83
Outer diameter [mm]:	90
Built-in diameter [mm]:	68-75
Voltage type:	AC
Dimming phase cut-off:	tak
Colour temperature adjustable:	Krokowo
Other features:	2 sposoby montażu - natynkowy i podtynkowy





