

## ASTAR LED, Under-cabinet linear light, 360lm, 4000K, 2-pin connector, pass-through connection system, ON/OFF switch

**Adviti**

Marka: ADVITI | Symbol: AD-OL-6425LZM4/PZ | Ean: 5908254840371



### PRODUCT DESCRIPTION

The E27 lamp holder ring is a component that is used to fix a lampshade to the fixture of a lamp. The product is made of white plastic. Thanks to the use of the ring, we can easily mount and disassemble the lampshade on the E27 holder, and if necessary, also replace the ring itself.

## TECHNICAL DATA

### General information:

|  |                                   |
|--|-----------------------------------|
| Nominal voltage [V]:                                 | 230                               |
| Lamp type:   | LED, niewymienne                  |
| Suitable for lamp power [W]:                         | 4                                 |
| Rated luminous flux according to IEC 62722-2-1 [lm]: | 360                               |
| Luminaire efficacy [lm/W]:                           | 90                                |
| With light source:                                   | tak                               |
| Colour temperature [K]:                              | 4000                              |
| Max. power [W]:                                      | 4                                 |
| Rated life time L70/B50 at 25 °C [h]:                | 15000                             |
| Colour rendering index CRI:                          | 80-89                             |
| Energy efficiency class of the built-in lamp:        | F                                 |
| Colour of light:                                     | Neutralny biały                   |
| Power factor:  | 0.5                               |
| Flickering value Pst LM:                             | 0.158                             |
| Stroboscope effect value SVM:                        | 0.15                              |
| Degree of protection (IP):                           | IP20                              |
| Impact strength:                                     | IK02                              |
| Protection class:                                    | II                                |
| Suitable for surface mounting:                       | tak                               |
| Suitable for light line configuration:               | tak                               |
| Material housing:                                    | Tworzywo sztuczne                 |
| Colour housing:                                      | Biały                             |
| Material cover:                                      | Tworzywo sztuczne matowe/satynowe |
| Width [mm]:  | 22                                |
| Height/depth [mm]:                                   | 32                                |
| Length [mm]:   | 305                               |

Type of wiring:

Końcowe



