

## ASTAR LED 7W, linear fixture with cable for installation under the cabinet, 630lm, 4000K, ON/OFF switch

**Adviti**Marka: **ADVITI** | Symbol: **AD-OL-6426LZM4/PZ** | Ean: **5908254829222**

### PRODUCT DESCRIPTION

The line of linear fixtures ASTAR LED consists of under-cabinet lamps designed to provide supplementary lighting for worktops e.g. in the kitchen, or in any place that would need more lumens. The parts are made out of white plastic in satin, semi-matte finish. The ASTAR under-cabinet lamps come equipped with non-replaceable LED light sources and inbuilt switches (ON/OFF with no possibility to regulate the intensity of light). ASTAR LED 7W is a linear fixture with two-pin plug and pass-through connector system, capable of emitting light of 630 lm intensity and color temperature of 4000K, so a neutral color. The dimensions of the

under-cabinet fixture are: 22 mm x 32 mm x 570 mm.

## TECHNICAL DATA

### General information:

|   |                      |
|---|----------------------|
| Nominal voltage:                                | 230 V                |
| Lamp type:                                      | LED, not replaceable |
| Suitable for lamp power:                        | 7 W                  |
| Rated luminous flux according to IEC 62722-2-1: | 630 lm               |
| With light source:                              | Yes                  |
| Colour temperature:                             | 4000 K               |
| Max. power:                                     | 7W                   |
| Rated life time L70/B50 at 25 °C:               | 15000 h              |
| Colour rendering index CRI:                     | >80                  |
| Material housing:                               | Plastic              |
| Energy efficiency class of the built-in lamp:   | F                    |
| Degree of protection (IP):                      | IP20                 |
| Colour of light:                                | Neutral              |
| Flickering value Pst LM:                        | 0.16                 |
| Stroboscope effect value SVM:                   | 0.15                 |
| Impact strength:                                | IK02                 |
| Protection class against electric shock:        | II                   |
| Suitable for surface mounting:                  | Yes                  |
| Suitable for light line configuration:          | Yes                  |
| Colour housing:                                 | White                |
| Material cover:                                 | Matt / satin plastic |
| Width:  | 22 mm                |
| Height/depth:                                   | 32 mm                |
| Length:   | 570 mm               |

|                     |            |
|---------------------|------------|
| Luminaire efficacy: | 90 lm/W    |
| Type of wiring:     | End wiring |