

ARTUS LED under-cabinet lamp, 3W, 225lm, 4000K, grey

Marka: **ADVITI** | Symbol: **AD-OM-6474L4/G** | Ean: **5908254841286**

Adviti



PRODUCT DESCRIPTION

A single ARTUS LED under-cabinet lamp in grey with 3W and a luminous flux of 225lm. The model emits light with a pleasant neutral colour of 4000K.

The modern design with a luminous surface in the form of a frame is ideal for both residential premises to illuminate kitchen worktops or shadowy corners of dressing rooms and in commercial interiors to illuminate workspaces. This type of lighting is designed to be mounted to the bottom surface of a shelf or cabinet.

The luminaire has a single through-wiring with a self-locking connector. The power supply is not included.

A single light can be used as an extension to the set. The series includes single lights without an on/off switch, single lights with an on/off switch and USB port, as well as a set of 3 (2x without an on/off switch, 1x with an on/off switch).

TECHNICAL DATA

General information:

Nominal voltage [V]:	12
Lamp type:	LED, niewymienne
Suitable for lamp power [W]:	3
Rated luminous flux according to IEC 62722-2-1 [lm]:	225
Luminaire efficacy [lm/W]:	75
With light source:	tak
Colour temperature [K]:	4000
Max. Power [W]:	3
Beam angle:	Wiązka bardzo szeroka > 80°
Rated life time L70/B50 at 25 °C [h]:	20000
Colour rendering index CRI:	80-89
Energy efficiency class of the built-in lamp:	G
Colour of light:	Neutralny biały
Flickering value Pst LM:	<1
Stroboscope effect value SVM:	<0,4
Degree of protection (IP):	IP20
Impact strength:	IK08
Protection class:	II
Suitable for surface mounting:	tak
Material housing:	Tworzywo sztuczne
Colour housing:	Szary

Material cover:	Tworzywo sztuczne matowe/satynowe
Width [mm]:	65
Height/depth [mm]:	50
Length [mm]:	160
Voltage type:	DC
Exchangeable control gear:	tak
Type of wiring:	Z okablowaniem przelotowym
Connection type:	Wtykowe samozaciskowe



