

## ARTUS LED under-cabinet lamp set, 3x3W, 3x225lm, 4000K, with touch switch and USB, black

**Adviti**Marka: **ADVITI** | Symbol: **AD-OM-6475L4/B** | Ean: **5908254841330**

### PRODUCT DESCRIPTION

Set of 3 ARTUS LED under-cabinet lamps in black, 3W with a luminous flux of 225lm each. They emit light with a pleasant neutral colour of 4000K. One of the three lamps has a touch-sensitive switch, which controls the operation of the entire set and adjusts the brightness of the light by holding the switch with your hand. In addition, the light has a built-in USB C port (5V 2.4A), which makes it easy to charge other electrical devices such as a phone or tablet.

The modern design with a luminous surface in the form of a frame is ideal for both residential premises to illuminate kitchen worktops or shadowy corners of dressing rooms and in commercial interiors to illuminate workspaces. This type of lighting is designed to be mounted to the bottom surface of a shelf or cabinet.

Power supply unit included. Lights also available in grey.

Single lamps are also available to expand the set.

## TECHNICAL DATA

### General information:

|  |                             |
|--|-----------------------------|
| Nominal voltage [V]:                                 | 230/12                      |
| Lamp type:   | LED, niewymienne            |
| Suitable for lamp power [W]:                         | 3x3                         |
| Rated luminous flux according to IEC 62722-2-1 [lm]: | 3x225                       |
| Luminaire efficacy [lm/W]:                           | 75                          |
| Suitable for number of lamps:                        | 3                           |
| With light source:                                   | tak                         |
| Colour temperature [K]:                              | 4000                        |
| Beam angle:  | Wiązka bardzo szeroka > 80° |
| Rated life time L70/B50 at 25 °C [h]:                | 20000                       |
| Colour rendering index CRI:                          | 80-89                       |
| Energy efficiency class of the built-in lamp:        | G                           |
| Colour of light:                                     | Neutralny biały             |
| Flickering value Pst LM:                             | <1                          |
| Stroboscope effect value SVM:                        | <0,4                        |
| Degree of protection (IP):                           | IP20                        |
| Impact strength:                                     | IK08                        |
| Protection class:                                    | II                          |
| Suitable for surface mounting:                       | tak                         |
| Material housing:                                    | Tworzywo sztuczne           |

|                            |   |
|----------------------------|---|
| Colour housing:            | Czarny                                  |
| Material cover:            | Tworzywo sztuczne matowe/satynowe       |
| Width [mm]:                | 65                                      |
| Height/depth [mm]:         | 50                                      |
| Length [mm]:               | 160                                     |
| Voltage type:              | AC/DC                                   |
| Exchangeable control gear: | tak                                     |
| Max. system power:         | 21                                      |
| Type of wiring:            | Końcowe                                 |
| Connection type:           | Wtyczka                                 |
| Other features:            | Port USB C 5V 2,4A; funkcja ściemniania |



