

## PIRAMIS LED under-cabinet lamp 3.5W, 200lm, 4000K, black

Marka: **ADVITI** | Symbol: **AD-OM-6563L4/B** | Ean: **5908254845284**

**Adviti**



### PRODUCT DESCRIPTION

The under-cabinet lamp PIRAMIS LED is a perfect lighting solution combining functionality with modern, elegant design. It is excellent as an additional under-cabinet lighting or as a spotlight illuminating worktops during kitchen works. It is also suitable for illuminating furniture, display cases, shelves and cabinets in living rooms or bedrooms. Thanks to its modern housing it is a subtle and simultaneously useful element of the interior.

It has a 3,5W LED light source, which emits a luminous flux of 200lm and guarantees adequate illumination of the working space. The colour temperature of 4000K ensures neutral white light, which is pleasant and does not strain eyes. The wide beam angle facilitates even light dispersion.

The PIRAMIS LED lamp has a modern and minimalistic design. Its flat triangular shape slightly protrudes from the cabinet surface and is almost unnoticeable. As it is available in two colour variants (grey and black), the lamp may be adjusted to different types of interiors. It is made of durable plastic with a matt satin finish.

The installation of the lamp is extremely easy, thanks to surface mounting and the use of self-clamping connectors. The 12 V DC power supply is safe for the user and the pass-through wiring makes it easy to connect several lamps into one set (4 socket connector, AD-OM-6601CN, also available in our offer). The lamp is intended for use in dry rooms (IP20).

The lamp's dimensions measure 124x10,5x150 mm. Black colour.

Available also with a built-in touchless switch.

## TECHNICAL DATA

### General information:

Nominal voltage [V]:	12
Lamp type:	LED, niewymienne
Suitable for lamp power [W]:	3.5
Rated luminous flux according to IEC 62722-2-1 [lm]:	200
With light source:	tak
Colour temperature [K]:	4000
Beam angle:	Wiązka bardzo szeroka > 80°
Rated life time L70/B50 at 25 °C [h]:	54000
Colour rendering index CRI:	90-100
Energy efficiency class of the built-in lamp:	F
Colour of light:	Neutralny biały
Degree of protection (IP):	IP20
Impact strength:	IK01
Protection class:	III

Suitable for surface mounting:	tak
Material housing:	Tworzywo sztuczne
Colour housing:	Czarny
Material cover:	Tworzywo sztuczne matowe/satynowe
Width [mm]:	124
Height/depth [mm]:	10.5
Length [mm]:	150
Voltage type:	DC
Exchangeable control gear:	nie
Type of wiring:	Z okablowaniem przelotowym
Connection type:	Wtykowe samozaciskowe