







AGAT LED 15W, garden luminiare, 1100lm, IP54, 4000K, black

Marka: ADVITI | Symbol: AD-OP-6112BLPM4 | Ean: 5908254817526

Adviti



PRODUCT DESCRIPTION

A garden luminaire with a simple round shape with a neat, polycarbonate lampshade, which perfectly illuminates interior of rooms, staircases, as well as the entrance to the building, driveway, terrace or garden arbors. This outdoor lamp can be mounted on the walls of buildings and even on fences. Several identical luminaires mounted at a distance or next to one another will create an interesting and coherent visual effect, and the entrance to the house or office building will be beautifully presented. The luminaire uses SMD LEDs, which guarantee high energy efficiency and have a long service life, because they shine up to 50,000 hours.









The presented garden lamp works with rated power of 15W and emits light with luminous flux of 1100 lm. It shines with a natural white color, with a temperature of 4000K. The degree of ingress protection IP54 guarantees sufficient protection against dust and water, so this garden luminaire will easily withstand even more difficult weather conditions. The lamp is available in white, gray and black.

TECHNICAL DATA

General information:

| Place of application: | Inside and out |
|---|----------------|
| Possibility of cooperation with a dimmer: | No |
| Durability L70/B50: | 50000 h |
| Connection type: | Screw cube |
| The minimum distance from the illuminated object: | 0,5 m |
| Luminous flux: | 1100 lm |
| Rated power: | 15 W |
| Light source: | LED SMD |
| Degree of protection (IP): | 54 |
| Colour temperature: | 4000 |
| Beam angle: | 320° |
| Nominal voltage: | 230V~, 50Hz |
| Colour: | black |
| Solar panel: | No |
| Dimensions - width: | 210 mm |
| Dimensions - height: | 49 mm |
| Colour rendering index CRI: | 85 |
| Material housing: | PC |
| Material of the lampshade: | PC |
| Control of the motion sensor: | No |
| Number of on / off cycles: | 100000 |
| Protection class against electric shock: | П |







| Operating temperature: | - 20 ~ 40°C |
|--|-------------|
| Adjustable daylight sensor (LUX): | No |
| Adjustable time setting (TIME): | No |
| Adjustment of motion detection range (SENS): | No |















