

## DALIA bollard garden luminaire with motion sensor, E27, max. 15W, IP54, 80 cm, black

**Adviti**Marka: **ADVITI** | Symbol: **AD-OP-6568BE27SMR** | Ean: **5908254845413**

### PRODUCT DESCRIPTION

The DALIA luminaire series is a perfect solution for those who want to create consistent, elegant, and above all, functional illumination outside their house. A modern design of each lamp, simple shape with black aluminium housing as well as milky glass lampshade make DALIA smoothly adapt to numerous arrangements.

The series offers diverse luminaires, such as facade fixtures and bollard lamps, with or without motion sensor, thus enabling the users to compose their own comprehensive illumination of a building, garden, terrace or

balcony. As the light sources are not included, the users may choose the bulb to adjust intensity and colour of the light to their own needs.

Each lamp has increased IP54 rate, which ensures durability and resistance to difficult weather conditions.

The presented DALIA luminaire is a bollard with motion sensor meant for one E27 bulb (bulb not included) with max. power of 15W. The bollard may be installed in order to illuminate a property, driveway, gate or house entrance. Such lighting significantly increases the safety of the household members. The supply voltage is 230V.

The built-in motion sensor turns the light on only when it is necessary – the moment the motion is detected (the detection range is 8m).

The height is 800mm. The diameter measures 90mm. Available also without motion sensor.

## TECHNICAL DATA

### General information:

Nominal voltage [V]:	230
Lamp type:	Żarówka
Suitable for lamp power [W]:	15
Lamp holder:	E27
With light source:	nie
Suitable for number of lamps:	1
Degree of protection (IP):	IP54
Protection class:	I
Type of luminaire:	Słupek oświetleniowy
Material housing:	Aluminium
Colour housing:	Czarny
Material cover:	Szkło matowe/satynowe
With light sensor:	tak
With movement sensor:	tak
Detection range [m]:	10

Adjustable daylight sensor :	tak
LUX light adjustment range:	0-1000 lux
Adjustable time setting :	tak
TIME adjustment range:	8s±5s - 12min±2min
Height/depth [mm]:	800
Diameter [mm]:	90
Voltage type:	AC