

PACHIRA LED 9W, garden luminaire with motion sensor, 500lm, IP54, 4000K, black

Adviti

Marka: **ADVITI** | Symbol: **AD-OP-6576BLPMR4** | Ean: **5908254845536**



PRODUCT DESCRIPTION

The garden luminaire PACHIRA LED is a reliable source of light that works well as illumination of a building facade, balcony or terrace, as well as it will illuminate access to the property.

It is equipped with LED technology that ensures energy efficiency and long service life, and the luminous flux of 500lm and power of 9W guarantee optimal lighting conditions. The colour temperature of 4000K allows to enjoy pleasant neutral light that would create an atmosphere perfect for evening relaxation in the garden.

The luminaire is resistant to weather conditions. Thanks to safe IP54 rate construction it guarantees reliability even in the most demanding conditions.

Black aluminium housing combined with milky plastic lampshade easily fits in every architecture.

The PACHIRA LED is equipped with motion sensor that boosts the convenience of use. The lamp automatically reacts for the movement detected nearby and is activated only when it is necessary. The detection range is max. 8m. Additionally, the adjustment of lighting time and the light allows to adapt the operation of the luminaire to specific environmental conditions and user preferences. This, on the other hand, contributes to electricity savings and extends the service life of light sources.

The dimensions of the luminaire measure 210x63x80mm. The garden luminaire is also available without motion sensor.

TECHNICAL DATA

General information:

Nominal voltage [V]:	230
Lamp type:	LED, niewymienne
Suitable for lamp power [W]:	9
Rated luminous flux according to IEC 62722-2-1 [lm]:	500
With light source:	tak
Colour temperature [K]:	4000
Beam angle:	Wiązka bardzo szeroka > 80°
Rated life time L70/B50 at 25 °C [h]:	30000
Colour rendering index CRI:	80-89
Energy efficiency class of the built-in lamp:	F
Colour of light:	Neutralny biały
Degree of protection (IP):	IP54
Protection class:	I
Type of luminaire:	Oprawa elewacyjna
Material housing:	Aluminium
Colour housing:	Czarny

Material cover:	Tworzywo sztuczne matowe/satynowe
With light sensor:	tak
With movement sensor:	tak
Detection range [m]:	8
Adjustable daylight sensor :	tak
LUX light adjustment range:	<3-2000 lux
Adjustable time setting :	tak
TIME adjustment range:	10s±5s - 5min ±1min
Adjustable detection range:	nie
The minimum distance from the illuminated object [m]:	0.5
Width [mm]:	210
Height/depth [mm]:	63
Length [mm]:	80
Number of switching cycles:	20000
Voltage type:	AC
Exchangeable control gear:	nie