

ASPEN LED 15W, garden luminaire with PIR motion sensor, 1300lm, IP65, 4000K, black

Marka: **ADVITI** | Symbol: **AD-OP-6604BLPMR4** | Ean: **5908254849763**

Adviti



PRODUCT DESCRIPTION

ASPEN LED is a modern garden luminaire equipped with a PIR motion sensor, which perfectly illuminates any space around the house. Thanks to the sensor, the lamp only switches on when needed, allowing for efficient energy management and increasing the comfort of use.

The luminaire has a luminous flux of 1300lm and an output of 15W, providing sufficient lighting for outdoor spaces. The colour temperature of 4000K generates neutral light and the wide light beam allows even

illumination of large areas, such as a terrace, building wall or property driveway.

The lamp has a twilight sensor, adjustable within <3-2000 lux, which, depending on the settings, only switches on the lamp after dark or also during the day. In addition, the lamp has an adjustable switching time between 10s-5min, allowing the light to be adapted to the user's needs. The detection range of the motion sensor is 9m.

The lamp has a modern, rounded shape that gives it an aesthetically pleasing look to suit a variety of styles. The black housing is made of high-quality plastic and the matt lamp shade ensures even light dispersion. The high protection rate (IP65) provides resistance to adverse weather conditions, including rain and dust, making it ideal for outdoor use, regardless of the weather.

Dimensions: 175x72x182 mm. The luminaire is available in three colours - white, black and grey.

TECHNICAL DATA

General information:

Nominal voltage [V]:	230
Lamp type:	LED, niewymienne
Suitable for lamp power [W]:	15
Rated luminous flux according to IEC 62722-2-1 [lm]:	1300
With light source:	tak
Colour temperature [K]:	4000
Beam angle:	Wiązka bardzo szeroka > 80°
Rated life time L70/B50 at 25 °C [h]:	50000
Colour rendering index CRI:	80-89
Energy efficiency class of the built-in lamp:	F
Colour of light:	Neutralny biały
Degree of protection (IP):	IP65
Impact strength:	IK10
Protection class:	II
Type of luminaire:	Oprawa elewacyjna
Material housing:	Tworzywo sztuczne

Colour housing:	Czarny
Material cover:	Tworzywo sztuczne matowe/satynowe
With light sensor:	tak
With movement sensor:	tak
Detection range [m]:	9
Adjustable daylight sensor :	tak
LUX light adjustment range:	<3-2000lux
Adjustable time setting :	tak
TIME adjustment range:	min.: 10 sek. \pm 3 sek., max.: 5min. \pm 1min
The minimum distance from the illuminated object [m]:	0.5
Width [mm]:	174.5
Height/depth [mm]:	72
Length [mm]:	181.5
Voltage type:	AC
Exchangeable control gear:	nie