

PORFIR II LED 5W/7W/10W, wall light with house number, IP65, 4000K, IK10

Adviti

Marka: **ADVITI** | Symbol: **AD-OP-6606LPM4** | Ean: **5908254851032**



65a

PRODUCT DESCRIPTION

The PORFIR II LED wall light with illuminated house number is designed for installation on building facades and concrete fences. The LED technology ensures even light distribution, energy efficiency and a long service life.

The lamp is suitable for 230V operation. It is equipped with a 3-position power adjustment (5W, 7W or 10W), which corresponds to a luminous flux of 700, 1000 and 1400 lm, allowing the light to be adapted to the user's needs. The lamp emits light with a pleasant neutral colour of 4000K.

A built-in twilight sensor allows to automatically adapt the lamp's operation to the surroundings, activating it only when necessary, so that the house number remains clearly visible regardless of the lighting conditions. The light intensity may be adjusted within the range of <3–50 lux.

A high IP65 rate ensures that the luminaire can withstand harsh weather conditions, while IK10 rate protects the luminaire from damage.

The product is designed for surface-mounting. The housing made of high-quality white plastic and the matt lamp shade guarantee durability and an aesthetically pleasing look.

The pack includes a set of stickers with letters and numbers to personalise the house number.

Dimensions: 300x195x52 mm.

TECHNICAL DATA

General information:

Nominal voltage [V]:	230
Lamp type:	LED, wymienne
Suitable for lamp power [W]:	5/7/10
Rated luminous flux according to IEC 62722-2-1 [lm]:	700/1000/1400
With light source:	tak
Colour temperature [K]:	4000
Rated life time L70/B50 at 25 °C [h]:	50000
Colour rendering index CRI:	80–89
Energy efficiency class of the built-in lamp:	F
Colour of light:	Neutralny biały
Degree of protection (IP):	IP65
Impact strength:	IK10
Protection class:	II
Suitable for wall mounting:	tak
Suitable for surface mounting:	tak
Material housing:	Tworzywo sztuczne

Colour housing:	Biały
Material cover:	Tworzywo sztuczne matowe/satynowe
With light sensor:	tak
Adjustable daylight sensor :	tak
LUX light adjustment range:	<3-50lux
Width [mm]:	300
Height/depth [mm]:	52
Length [mm]:	195
Voltage type:	AC
Exchangeable control gear:	tak