

## ZONDA LED 16W, ceiling light with motion sensor, 1100lm, IP20, 4000K, milky PC, white

**Adviti**Marka: **ADVITI** | Symbol: **AD-PL-6076WLPMR4** | Ean: **5908254817625**

### PRODUCT DESCRIPTION

This ceiling light is designed to automatically illuminate rooms such as: staircases, corridors, basements, garages, warehouses, cloakrooms, etc. This lighting fixture has a neatly built-in PIR motion sensor, which is placed in the center and, depending on the settings, it will detect even the smallest movement. The twilight sensor (depending on the settings) switches on the lighting only when it is needed. Thanks to the two potentiometers, the sensor can be set according to the needs so as to operate exactly when people are present or they are moving in a given area. The settings include: lighting time in the range from 10 seconds to

3 minutes and light intensity. The maximum range of motion detection is 6 m. The luminaire uses SMD LED diodes, which guarantee high energy efficiency and have a long service life. The presented lamp works with rated power of 16 W and emits light with luminous flux of 1100 lm. It shines with a natural white color at a temperature of 4000K. The base of the lamp is made of a metal alloy, and the lamp shade is entirely made of unbreakable polycarbonate in a milky color.

## TECHNICAL DATA

### General information:

<b>Luminous flux:</b>	1100 lm
<b>Rated power:</b>	16 W
<b>Light source:</b>	LED SMD
<b>Degree of protection (IP):</b>	20
<b>Colour temperature:</b>	4000
<b>Nominal voltage:</b>	230V~, 50Hz
<b>Colour:</b>	white
<b>Dimensions - depth:</b>	67 mm
<b>Dimensions - width:</b>	290 mm
<b>Dimensions - height:</b>	290 mm
<b>Colour rendering index CRI:</b>	>85
<b>Detection angle:</b>	360°
<b>Material of the lampshade:</b>	polycarbonate
<b>Control of the motion sensor:</b>	No
<b>Type of sensor:</b>	PIR
<b>Detection range:</b>	6 m
<b>Adjustable daylight sensor (LUX):</b>	Yes
<b>Daylight sensor adjustment range (LUX):</b>	<3–2000lux
<b>Adjustable time setting (TIME):</b>	Yes
<b>Lighting time adjustment range (TIME):</b>	min: 10 sek. ± 3 sek.; max: 3 min. ± 30 sek.
<b>Adjustment of motion detection range (SENS):</b>	No



