

KOKO LED luminaire with microwave motion sensor, 12W, 3000K, 1100lm, black-polypropylene, matt PC diffuser, IP44, IK10

Adviti

Marka: **ADVITI** | Symbol: **AD-PL-6257BLPMM3** | Ean: **5904988902910**



PRODUCT DESCRIPTION

Luminaire designed for illumination of staircases, corridors, verandas, cellars, utility rooms, facades, etc. The modern LEDs used guarantee high energy efficiency and a long service life. The impact-resistant diffuser is made of high-quality polycarbonate. The base is available in black. The luminaire additionally has a built-in microwave motion sensor and twilight sensor, so it only switches on the lighting when it is needed.

TECHNICAL DATA

General information:

Outer diameter:	330 mm
Nominal voltage:	230 V
Lamp type:	LED, not replaceable
Suitable for lamp power:	12 W
Rated luminous flux according to IEC 62722-2-1:	1100 lm
With light source:	Yes
Colour temperature:	3000 K
Max. power:	12W
Rated life time L70/B50 at 25 °C:	25000 h
Colour rendering index CRI:	>80
Standby power:	12 W
Material housing:	Plastic
Energy efficiency class of the built-in lamp:	F
Degree of protection (IP):	IP44
Colour of light:	Warm
Power factor:	1
Flickering value Pst LM:	0.1
Stroboscope effect value SVM:	0.1
Impact strength:	IK10
Protection class against electric shock:	II
Suitable for wall mounting:	Yes
Suitable for ceiling mounting:	Yes
Suitable for surface mounting:	Yes
Colour housing:	Black
Material cover:	Matt / satin plastic
With movement sensor:	Yes

Type of sensor:	Microwave
Detection range:	2-8 m
Adjustable daylight sensor (LUX):	Yes
Daylight sensor adjustment range (LUX):	5lux, 30lux, 150lux, 2000lux
Adjustable time setting (TIME):	Yes
Lighting time adjustment range (TIME):	5 sek., 30 sek., 90 sek., 3 min., 5 min., 10 min.
Adjustment of motion detection range (SENS):	Yes
Height/depth:	110 mm



