

KOKO LED luminaire with PIR motion sensor, 12W, 3000K, 1100lm, silver-polypropylene, matt PC diffuser, IP44, IK10



Marka: ADVITI | Symbol: AD-PL-6257GLPMR3 | Ean: 5904988902958



PRODUCT DESCRIPTION

Luminaire designed for illumination of staircases, corridors, verandas, cellars, utility rooms, facades, etc. The modern LEDs used guarantee high energy efficiency and long service life. The impact-resistant diffuser is made of high-quality polycarbonate. The base is available in silver. The luminaire additionally has a built-in PIR (infrared motion detector) and twilight sensor, so it only switches on the lighting when it is needed.



TECHNICAL DATA

General information:

Outer diameter:	330 mm
Nominal voltage:	230 V
Lamp type:	LED, not replaceable
Suitable for lamp power:	12 W
Rated luminous flux according to IEC 62722-2-1:	1100 lm
With light source:	Yes
Colour temperature:	3000 K
Max. power:	12W
Rated life time L70/B50 at 25 °C:	25000 h
Colour rendering index CRI:	>80
Material housing:	Plastic
Energy efficiency class of the built-in lamp:	F
Degree of protection (IP):	IP44
Colour of light:	Neutral
Power factor:	1
Flickering value Pst LM:	0.1
Stroboscope effect value SVM:	0.1
	0.1
Impact strength:	IK10
Impact strength: Protection class against electric shock:	
	IK10
Protection class against electric shock:	IK10 II
Protection class against electric shock: Suitable for wall mounting:	IK10 II Yes
Protection class against electric shock: Suitable for wall mounting: Suitable for ceiling mounting:	IK10 II Yes Yes
Protection class against electric shock: Suitable for wall mounting: Suitable for ceiling mounting: Suitable for surface mounting:	IK10 II Yes Yes Yes
Protection class against electric shock:Suitable for wall mounting:Suitable for ceiling mounting:Suitable for surface mounting:Colour housing:	IK10 II Yes Yes Yes Silver



Detection range:	3-6 m
Adjustable daylight sensor (LUX):	Yes
Daylight sensor adjustment range (LUX):	10lux or 2000lux
Adjustable time setting (TIME):	Yes
Lighting time adjustment range (TIME):	5 sek., 30 sek., 1 min., 3 min., 5 min., 8 min.
Adjustment of motion detection range (SENS):	Yes
Height/depth:	110 mm

(T











