

**KOKO LED luminaire with microwave motion sensor, 18W,
3000K, 1650lm, silver-polypropylene, matt PC diffuser,
IP44, IK10**

Adviti

Marka: **ADVITI** | Symbol: **AD-PL-6280GLPMM3** | Ean: **5904988903108**



PRODUCT DESCRIPTION

Luminaire designed for lighting staircases, corridors, verandas, cellars, utility rooms, facades, etc. The modern LEDs used guarantee high energy efficiency and long service life. The impact-resistant diffuser is made of high-quality polycarbonate. The base is available in silver colour. The luminaire additionally has a built-in microwave motion sensor and twilight sensor, so it only switches on the lighting when it is needed.

TECHNICAL DATA

General information:

| | |
|---|----------------------|
| Outer diameter: | 330 mm |
| Nominal voltage: | 230 V |
| Lamp type: | LED, not replaceable |
| Suitable for lamp power: | 18W W |
| Rated luminous flux according to IEC 62722-2-1: | 1650 lm |
| With light source: | Yes |
| Colour temperature: | 3000 K |
| Max. power: | 18W |
| Rated life time L70/B50 at 25 °C: | 25000 h |
| Colour rendering index CRI: | >80 |
| Material housing: | Plastic |
| Energy efficiency class of the built-in lamp: | F |
| Degree of protection (IP): | IP44 |
| Colour of light: | Warm |
| Power factor: | 1 |
| Flickering value Pst LM: | 0.1 |
| Stroboscope effect value SVM: | 0.1 |
| Impact strength: | IK10 |
| Protection class against electric shock: | II |
| Suitable for wall mounting: | Yes |
| Suitable for ceiling mounting: | Yes |
| Suitable for surface mounting: | Yes |
| Colour housing: | Silver |
| Material cover: | Matt / satin plastic |
| With movement sensor: | Yes |
| Type of sensor: | Microwave |

| | |
|--|---|
| Detection range: | 2-8 m |
| Adjustable daylight sensor (LUX): | Yes |
| Daylight sensor adjustment range (LUX): | 5lux, 30lux, 150lux, 2000lux |
| Adjustable time setting (TIME): | Yes |
| Lighting time adjustment range (TIME): | 5 sek., 30 sek., 90 sek., 3 min., 5 min., 10 min. |
| Adjustment of motion detection range (SENS): | Yes |
| Height/depth: | 110 mm |