

VITO LED Ceiling light 36W, 3500lm, IP20, 3000/4000/6500K + RGB, Tuya app

AdvitiMarka: **ADVITI** | Symbol: **AD-PL-6515WLZM/CCT** | Ean: **5908254843341**

PRODUCT DESCRIPTION

The modern 36W VITO LED ceiling light is an innovative solution combining both functionality and aesthetics. A luminous flux of 3500lm guarantees an adequate illumination of a room. Thanks to the LED technology the ceiling lamp is a practical source of light. Its oval shape and thin body fit ideally in every interior.

The lamp has two sources of light – a LED panel and a LED RGB strip.

The main LED panel ensures the basic illumination of a room as well as regulation of both temperature of the light and its intensity. Thanks to it the user may easily create the desired atmosphere depending on their needs – ranging from toned colour temperature of 3000K to dynamic and strong light of 6000K.

On the other hand, the LED strip placed in the upper part emits colourful RGB light and enables the user to choose from diverse colours and lighting modes – smooth transitions or rapid changes. In this way, you may create a dedicated atmosphere of a room that takes on an individual character.

The LED panel and the LED RGB strip may work simultaneously, creating effective light combinations, or separately, meeting precise expectations of the user.

You may adjust the light's parameters via application. The application enables to change the temperature, intensity and colour as well as to moderate the way the colours are displayed.

What is more, you may connect the lamp to a voice assistant. Thanks to this option the operation of the lamp is even more intuitive and practical.

The lamps diameter is 400 mm.

TECHNICAL DATA

General information:

Nominal voltage [V]:	230
Lamp type:	LED, wymienne
Suitable for lamp power [W]:	36
Rated luminous flux according to IEC 62722-2-1 [lm]:	3500
Luminaire efficacy [lm/W]:	97
With light source:	tak
Colour temperature [K]:	CCT+RGB
Rated life time L70/B50 at 25 °C [h]:	30000
Rated life time L80/B10 at 25 °C [h]:	15000
Colour rendering index CRI:	80-89
:	tak
Energy efficiency class of the built-in lamp:	F
Colour of light:	Wielobarwny

Power factor:	0.9
Flickering value Pst LM:	0.9
Stroboscope effect value SVM:	0.4
Degree of protection (IP):	IP20
Impact strength:	IK05
Protection class:	II
Suitable for wall mounting:	tak
Suitable for ceiling mounting:	tak
Suitable for surface mounting:	tak
Material housing:	Tworzywo sztuczne
Colour housing:	Biały
Material cover:	Tworzywo sztuczne matowe/satynowe
Height/depth [mm]:	25
Outer diameter [mm]:	400
Voltage type:	AC
Exchangeable control gear:	nie
Operation by Bluetooth:	tak
Compatible with Google Assistant:	tak
Compatible with Amazon Alexa:	tak
Compatible with TUYA:	tak



