

## LED strip 12V, Samsung chipset 2835, 60L/m, 630lm/m, 6W/m, IP20, 6000K, 5m

**Adviti**

Marka: **ADVITI** | Symbol: **AD-TL-6491L6** | Ean: **5908254842016**



### PRODUCT DESCRIPTION

LED lighting strip is a product with a wide range of applications. You may stick it to the desired surface or you may use LED profiles (recessed, surface-mounted, angled). Thanks to small size (it is only 8 mm wide) it is easy to install on the walls, furniture, near the mirror or even in the places where there is no traditional light e. g. wardrobe niches.

The band is equipped with 60 cool 6000K LED diodes per meter. Application of the LED strip is economical

and, on the other hand, efficient in terms of the amount of light generated. The usage is completely safe due to 12V DC supply voltage.

The IP20 LED strip will work in dry rooms, such as offices or walk-in wardrobes. It is 5 m long and may be cut every 5 cm in order to customize it to individual needs.

Connection to the relevant TUYA controller enables remote lighting control with the help of mobile application or voice assistant.

Controllers and other fixing accessories are available in our offer.

## TECHNICAL DATA

### General information:

|   |                  |
|---|------------------|
| Lamp voltage [V]:                             | 12               |
| Lamp type:                                    | LED, niewymienne |
| Lamp power per meter [W]:                     | 6                |
| Luminous flux per meter [lm]:                 | 630              |
| Model:  | Taśma            |
| Degree of protection (IP):                    | IP20             |
| PCB:  | Podwójne 8mm     |
| Chip type:                                    | SMD 2835         |
| Energy efficiency class of the built-in lamp: | F                |
| Max. system power [W]:                        | 30               |
| :   | 6                |
| Rated life time L70/B50 at 25 °C [h]:         | 30000            |
| Cycle on/off:                                 | 30000            |
| Colour temperature [K]:                       | 6000             |
| Colour of light:                              | Zimna biel       |
| Colour rendering index CRI:                   | 80-89            |
| Beam angle (°):                               | 120              |
| Number of nodes per meter:                    | 60               |

|                            |                                    |
|----------------------------|------------------------------------|
| Suitable for dimmer:       | tak                                |
| Cut every ... [cm]:        | 5                                  |
| Width [mm]:                | 8                                  |
| Height/depth [mm]:         | 2                                  |
| Length [mm]:               | 5000                               |
| Voltage type:              | DC                                 |
| Type of control gear:      | Sterownik LED sterowany napięciowo |
| Exchangeable control gear: | tak                                |
| Self-adhesive:             | tak                                |

