

SELENE ceiling light with microwave motion sensor, 2xE27, max. 2x60W, IP54, black

ViRONEMarka: **Virone** | Symbol: **CL/2XE27-10MV/B** | Ean: **5908254841460**

PRODUCT DESCRIPTION

SELENE wall and ceiling light in black with microwave motion sensor, with IP54 protection level for outdoor and indoor lighting with high humidity levels. The classic circular shape is suitable for both residential and commercial spaces, e.g. in the corridor, office or basement. The combination of several of the same SELENE lighting plafonds will certainly transform the arrangement of larger usable areas, such as conference rooms.

Lamp suitable for two replaceable light sources, i.e. bulbs with E27 thread, max. 60W. The bulbs are not

included, so you can adapt the parameters of the emitted light to your own needs. Equipped with a microwave motion sensor which is located inside the luminaire, depending on the settings it will detect even the slightest movement. The sensor allows adjustment of the lighting time between 3-10 seconds, light sensitivity (2lux, 10lux, 25lux, 50lux, off) and adjustment of motion detection between 1-4m.

The housing material consists of metal and plastic and the lampshade of matt/satin plastic. The diameter of the lamp is 30.5 cm.

The product also features a high degree of impact protection class - IK07.

Product also available in white and grey.

TECHNICAL DATA

General information:

Nominal voltage:	230
Lamp type:	Żarówka
Suitable for lamp power:	2x60
Lamp holder:	E27
Suitable for number of lamps:	2
With light source:	nie
Max. power:	2x60
Degree of protection (IP):	IP54
Impact strength:	IK07
Protection class:	I
Suitable for wall mounting:	tak
Suitable for ceiling mounting:	tak
Suitable for surface mounting:	tak
Material housing:	Metal/Tworzywo sztuczne
Colour housing:	Czarny
Material cover:	Tworzywo sztuczne matowe/satynowe
With movement sensor:	tak

With light sensor:	tak
Sensor type:	Mikrofalowy
Detection range:	1-4m
Adjustable daylight sensor :	2lux, 10lux, 25lux, 50lux, off
Adjustable time setting :	5s, 30s, 1min, 3min, 5min, 10min, 20min, 30min
Adjustable detection range:	1-4m
Height/depth:	90
Outer diameter:	305