

Splash-proof empty cable reel IP44 4x2P+E 16A 230V, H05VV-F 3x1.5mm², 50m

ViRONEMarka: **Virone** | Symbol: **CR-5** | Ean: **5908254846991**

PRODUCT DESCRIPTION

The splash-proof empty cable reel enables to safely and reliably connect more devices to a single extension cord. It is equipped with 4 French-type sockets (2P+E) with safety shutters, which ensure convenience and compatibility with various electrical appliances.

The cable reel has IP44 rate and is equipped with splash-proof covers which ensure dust and water resistance. It perfectly works in dry rooms, both at homes and in the offices, warehouses or halls, as well as

outdoors, e.g. in the garden, in more difficult weather conditions.

Thanks to its durable construction made from high-quality plastic and a thermal switch serving as overload protection, it ensures peace of mind and safety when connecting more appliances to one extension socket.

The recommended cable, 50m long with H05VV-F 3x1,5mm² specification and rubber insulation, provides, above all, flexibility and freedom of use, without worrying about being too far from an outlet. The cable reel has current protection which guarantees smooth operation even while intensive use.

A convenient handle for carrying as well as rotary drum winding handle provide ergonomics and comfort during transport.

The dimensions measure 280mm x 382mm x 132mm. Black-orange colour.

TECHNICAL DATA

General information:

Material housing:	Tworzywo sztuczne
Recommended Cable:	H05RR-F 3x1,5mm ²
Core cross section [mm²]:	1.5
Number of cores:	3
Max. cable length [m]:	50
With mounting frame:	Tak
With thermal protection:	Tak
With overload protection:	Tak
Degree of protection (IP):	IP44
Colour:	czarno-pomarańczowy
Supply voltage [V]:	230
Frequency [Hz]:	50
Current [A]:	16
Max. load for the extended wire [W]:	3680
Max. load for the reeled wire [W]:	1000
Socket type:	2P+Z

Socket standard:	french (type E)
Number of network sockets:	4
Shutters for current paths:	Tak
Dimensions - width [mm]:	280
Dimensions - height [mm]:	382
Dimensions - depth [mm]:	132
Insulation type:	Guma



