







Battery-powered carbon monoxide detector, 2xAA, sensor lifetime 10 years

Marka: Virone | Symbol: DC-10 | Ean: 5908254850578





PRODUCT DESCRIPTION

The battery-operated carbon monoxide detector is a modern alarm device intended for continuous control of carbon monoxide concentration. Suitable for indoor use, in spaces particularly exposed to hazards that may arise as a result of failure or lack of adequate ventilation.

The unit has a large LCD display that indicates the level of detected danger (carbon monoxide), as well as a low battery level and end of service life. It has a built-in electrochemical sensor that very precisely indicates







the carbon monoxide level using visual and sound notifications.

The product has an illuminated TEST button that allows to check the correct operation of the sensor.

A carbon monoxide detector should be placed at eye level in the most frequently used room, such as the kitchen, living room or hallway, in order to objectively assess the amount of carbon monoxide particles in the inhaled air.

The lifetime of the sensor is 10 years. The model is powered by two AA batteries (included). The dimensions measure: 126x77x34,2

Compliance with EN 50291-1:2018+AC:2021-01 and PN-EN 50291-1:2018-06+AC:2021-03 standards, confirmed by the TUV certification body.

TECHNICAL DATA

General information:

Standalone:	Tak
Current supply primary:	Bateria/akumulator
Supply voltage [V]:	3
Voltage type (supply voltage):	DC
Power supply:	2xAA (w zestawie)
Battery included:	Roztwór alkaliczny
Loudness [dB(A)]:	≥85db/3m
Place variable:	Tak
Length [mm]:	126
Width [mm]:	34.2
Height [mm]:	77
Colour:	Biały
Type of test-/pause button:	Przycisk testowy
Degree of protection (IP):	IP20
With digital display:	Tak

Page 2 / 4









Compliant standards:	EN 50291-1:2018+AC:2021-01; PN-EN 50291-1:2018-06+AC:2021-03
Certification authority:	TUV
Response temperature [°C]:	-10°C ~ +40°C
Storage temperature [°C]:	-20°C ~ +50°C
Battery Life:	5 lat
Sensor lifetime:	10 lat
Concentration range displayed:	25 [999PPM
Sensor Type:	Elektrochemiczny typ B
Alarm method:	Wizualne i dźwiękowe

















