

Battery-powered carbon monoxide detector, 2xAA, sensor lifetime 10 years

Marka: **Virone** | Symbol: **DC-11** | Ean: **5908254851223**

ViRONE


PRODUCT DESCRIPTION

The battery-operated carbon monoxide detector is a modern alarm device intended for continuous control of carbon monoxide concentration. Suitable for indoor use, in spaces particularly exposed to hazards that may arise as a result of failure or lack of adequate ventilation.

The unit has a large LCD display that indicates the level of detected danger (carbon monoxide), as well as a low battery level and end of service life. It has a built-in electrochemical sensor that very precisely indicates

the carbon monoxide level using visual and sound notifications. ventilation.

The product has an illuminated TEST button that allows you to check the correct operation of the sensor. ventilation.

A carbon monoxide detector should be placed at eye level in the most frequently used room, such as the kitchen, living room or hallway, in order to objectively assess the amount of carbon monoxide particles in the inhaled air. ventilation.

The lifetime of the sensor is 10 years. The model powered by two AA batteries (included). ventilation.

Compliance with EN 50291-1:2018+AC:2021-01 and PN-EN 50291-1:2018-06+AC:2021-03 standards, confirmed by the SGS certification body.

TECHNICAL DATA

General information:

Standalone:	Tak
Current supply primary:	Bateria/akumulator
Supply voltage [V]:	3
Voltage type (supply voltage):	DC
Power supply:	2xAA (w zestawie)
Battery included:	Roztwór alkaliczny
Loudness [dB(A)]:	≥85db/3m
Place variable:	Tak
Length [mm]:	93
Width [mm]:	28.5
Height [mm]:	93
Colour:	Biały
Type of test-/pause button:	Kombinowany
Degree of protection (IP):	IP20
With digital display:	Tak

Compliant standards:	EN 50291-1:2018+AC:2021-01; PN-EN 50291-1:2018-06+AC:2021-03
Certification authority:	SGS
Response temperature [°C]:	-10°C ~ +40°C
Sensor lifetime:	10 lat
Battery lifetime:	3 lata
Concentration range displayed:	0-999PPM
Sensor Type:	Elektrochemiczny typ B
Alarm method:	Wizualne i dźwiękowe
Standby curren [uA]:	<40uA
Alarm current [mA]:	<60uA