







Extension sockets 3x2P+E, 1.4m, H05VV-F, 3x1mm2, czarny

Marka: Virone | Symbol: ES-8/B/1,4 | Ean: 5908254847943





PRODUCT DESCRIPTION

Extension sockets are practical devices that are always worth having at hand. They are used to available power in places that are away from a mains socket. Additionally, they may also be used as a splitter. They enable several devices to be connected simultaneously to a single power source.

Use the extension socket successfully on your desk, for your computer, Christmas tree lights or during spring cleaning. Use your devices safely and easily wherever you want.









The 3-gang extension socket is easy-to-use and safe solution for offices and households. The product is black, equipped with 3 French-type mains sockets (2P+E), H05VV-F 3x1.5 mm2 cable 1,4 m long, flat plug with a comfortable handle, safety shutters, convenient hanger if you need to hang the device e.g. on the wall, PVC insulation. For indoor use (IP20).

The flat plug allows the unit to be plugged in easily and also prevents accidental damage, bending or breaking of the cable, even if the space is limited. We may also move the furniture closer to the wall. A comfortable handle allows to hold, easily unplug or plug the unit into a power source.

The device is suitable for a maximum load of 3680W (model without a switch). Available in two colour variants: black and white. Variants of extension sockets are also available - with a different cable length, number of sockets, with an on/off switch or in a different colour.

TECHNICAL DATA

General information:

Housing shape:	Prostokątny
Number of socket outlets French standard type E:	3
With on/off switch:	Nie
Safety shutters:	Tak
Nominal voltage [V]:	230
Frequency [Hz}:	50
Nominal current [A]:	10
Max. connected load [W]:	2300
Number of wires:	3
Core cross section [mm]:	1
Length of power cord [m]:	1.4
Type of cable:	H05VV-F
Type of insulation:	PVC
Material:	Tworzywo sztuczne
Material quality:	Tworzywo termoplastyczne
Surface finishing:	Matowy
Colour:	Czarny

Page 2 / 4









Degree of protection (IP):	IP20
Rotated central insert:	Tak
Angle rotated central insert:	45°
Operating temperature [°C]:	-10 do +40
Dimensions - width [mm]:	80
Dimensions - height [mm]:	235
Dimensions - depth [mm]:	61



















