

ALLED LED floodlight with PIR motion sensor 20W, 1500lm, IP44, 4000K, Alu+glass

VIRONEMarka: **Virone** | Symbol: **FL/R-1** | Ean: **5908254804748**

PRODUCT DESCRIPTION

This floodlight is of great use at homes and in other indoor spaces such as: garages, halls, etc. It can be also installed outside to provide light to parking areas, gardens or to illuminate building walls, signboards and billboards. This floodlight is equipped with LED SMD diodes which are the source of light and a PIR sensor that responds to motion. Taking into account ingress protection level of the device (IP44), it can be installed in rooms of increased humidity.

TECHNICAL DATA

General information:

| | |
|--|---|
| Luminous flux: | 1500 lm |
| Rated power: | 20 W |
| Light source: | LED SMD |
| Degree of protection (IP): | 44 |
| Colour temperature: | 4000K |
| Nominal voltage: | 230V~, 50Hz |
| Colour: | black |
| Dimensions - depth: | 165 mm |
| Dimensions - width: | 118 mm |
| Dimensions - height: | 48 mm |
| Colour rendering index CRI: | >80 |
| Detection angle: | 120° |
| Control of the motion sensor: | Yes |
| Adjustable daylight sensor (LUX): | Yes |
| Daylight sensor adjustment range (LUX): | <3–2000lux |
| Adjustable time setting (TIME): | Yes |
| Lighting time adjustment range (TIME): | min: 10 sek. ± 3 sek.; max: 5 min. ± 2 min. |
| Adjustment of motion detection range (SENS): | Yes |



