

ALLED LED floodlight with PIR-motion sensor 10W, 850lm, IP65, 4000K, Alu+Glass



Marka: **Virone** | Symbol: **FL/R-9** | Ean: **5908254844119**



PRODUCT DESCRIPTION

ALLED LED floodlight is the source of light which perfectly works on building facades, in the construction sites, workshops or garages. Suitable for indoor and outdoor use.

ALLED guarantees effective and comfortable lighting. It features relatively high power (10W) simultaneously being small in size. The LED source of light emits luminous flux of 850lm of pleasant 4000K colour temperature.

The floodlight is equipped with PIR motion sensor which enables switching on the device once the motion near it is detected. This solution is effective, increases comfort in use and simultaneously contributes to energy savings.

Its housing is made of aluminium which guarantees durability, and thanks to high ingress protection rate of IP65 the floodlight is resistant to every weather conditions.

The black aluminium housing and transparent lampshade made of durable glass as well as the lamp's compact dimensions (83x21x110mm) make it easily blend in multitude of spaces; thus, ensuring not only functionality but also aesthetic look.

The floodlight is suitable for wall and ceiling surface mounting. You may also mount it on a tripod to adjust the device to the user's needs.

TECHNICAL DATA

General information:

Nominal voltage [V]:	230
Lamp type:	LED, niewymienne
Suitable for lamp power [W]:	10
Luminous flux [lm]:	850
With light source:	tak
Colour temperature [K]:	4000
Rated life time L70/B50 at 25 °C [h]:	15000
Colour rendering index CRI:	80-89
Power factor:	>0,9
Energy efficiency class of the built-in lamp:	F
Colour of light:	Neutralny biały
Flickering value Pst LM:	<1
Stroboscope effect value SVM:	0.8
Degree of protection (IP):	IP44
Impact strength:	IK06
Protection class:	I

Suitable for surface mounting:	tak
Suitable for wall mounting:	tak
Suitable for ceiling mounting:	tak
:	tak
Material housing:	Aluminium
Material cover:	Szkło przezroczyste
Colour housing:	Czarny
With movement sensor:	tak
With light sensor:	tak
Sensor type:	PIR
Detection range:	2-10m
Adjustable daylight sensor :	tak
:	3-2000lux
Adjustable time setting :	tak
:	min. 10± 3 sek. - max. 5±2 min
Width [mm]:	142
Height/depth [mm]:	21
Length [mm]:	110
Exchangeable control gear:	tak



