

NOVA LED 9W, rechargeable work floodlight, 700lm, IP54, 4000K, 1800mAh

Marka: **Virone** | Symbol: **FLP-6** | Ean: **5908254850523**

ViRONE



PRODUCT DESCRIPTION

The portable rechargeable NOVA LED work floodlight is a compact and efficient light source, ideal to use in workshops, garages, basements or during renovations. The device effectively illuminates the workspace, providing comfortable conditions both inside and outside the building.

The 9W NOVA LED floodlight is ment for 5V DC supply voltage. The luminous flux of 700lm and a wide beam angle allow for effective illumination of the selected spot, and the built-in switch allows for quick and

convenient start-up. The 4000K colour temperature emits a pleasant neutral light that does not strain the eyes.

Additionally, the floodlight is equipped with a stable stand with a movable base, thanks to which one may precisely adjust the direction of the light. The non-slip rubber handle makes the device more comfortable to hold and carry.

The built-in 1800mAh Li-ion battery allows for continuous operation for 1 hour 45 minutes. It is charged via the USB-C port (charging cable included). The floodlight is equipped with a power cut-off switch that protects against battery discharge and against accidental switching on of the device, e.g. during transport.

Additionally, a diode indicator informs about the battery status – a green diode indicates a full charge, an orange diode indicates low power, and a red diode indicates that the device needs to be connected to a charger.

The IP54 protection class provides protection against dust and moisture, which means the floodlight can be used in various weather conditions.

The housing is made of high-quality plastic in black and orange colors, ensuring long-term use.

Its compact dimensions of 132x127x117 mm make NOVA LED easy to carry and convenient to transport.

TECHNICAL DATA

General information:

Nominal voltage [V]:	5
Lamp type:	LED, niewymienne
Battery capacity [mAh]:	1800
Type of battery:	Akumulator Li-ion
Battery included:	tak
Suitable for lamp power [W]:	9
Rated luminous flux according to IEC 62722-2-1 [lm]:	700
Colour temperature [K]:	4000
Beam angle:	Wiązka bardzo szeroka > 80°
Rated life time L70/B50 at 25 °C [h]:	25000
Colour rendering index CRI:	80-89

Colour of light:	Neutralny biały
Degree of protection (IP):	IP54
Protection class:	III
Material housing:	Tworzywo sztuczne
Material cover:	Tworzywo sztuczne przezroczyste
Colour housing:	Czarny/Pomarańczowy
Voltage type:	DC
With switch:	tak
The length of the power cord [m]:	1
Width [mm]:	127
Height/depth [mm]:	217
Length [mm]:	132
Other features:	Wejście ładowania USB-C (przewód w zestawie), czas pracy przy pełnym naładowaniu 1 h 45 min, przełącznik odcięcia zasilania