

## Mini LED COB flashlight, 500lm, 1200mAh, CCT

Marka: **Virone** | Symbol: **LT-25** | Ean: **5908254851261**

**ViRONE**



### PRODUCT DESCRIPTION

The 3W mini LED COB flashlight is perfect for use in workshops, garages, basements or while camping. LED COB technology ensures intense and even light dispersion, as well as high energy efficiency.

The built-in 1,200 mAh Li-ion battery is charged via a USB-C port (charging cable included), eliminating the need to replace the battery. The 4-stage charge indicator allows constant monitoring of the battery level.

The flashlight offers 6 operating modes: high, medium, low, red light, red flashing light and a turbo mode providing strong light up to 500 lm. In addition, the user may adjust the colour temperature – from warm to cold – in four levels: 2700K, 4000K, 6500K and 8000K. The illuminating range is up to 30 m.

The flashlight is equipped with a movable base that allows to precisely regulate the direction of the light. The built-in magnet and thread for an M6 screw allow the device to be securely mounted on metal surfaces or a small tripod. An additional hole for the pendant allows the device to be hung anywhere.

The product has an IPX4 protection rate. Its robust construction is made of plastic and aluminium in black and grey. The dimensions measure: 61x56x28 mm.

The flashlight is sold as a display of 8 pcs.

## TECHNICAL DATA

### General information:

Lamp type:	LED COB
Power [W]:	3
Luminous flux [lm]:	500
Power type:	Akumulator Li-ion
Battery capacity [mAh]:	1200
Battery type:	Akumulator zainstalowany na stałe
Number of batteries:	1
With batteries:	tak
Number of light modes:	6
Modes of operation:	Tryb mocny, tryb średni, tryb słaby, światło czerwone, światło czerwone pulsujące, tryb turbo + CCT
Rechargeable:	tak
Battery charge indicator:	tak
Light range [m]:	30
Color temperature [K]:	2700-4000-6500-8000
Color rendering index Ra/CRI:	65
Lifespan L70/B50 [h]:	30000

Number of switching cycles:	10000
Degree of protection (IP):	IPX4
Impact protection IK (shock resistance):	IK05
Model:	Robocze-warsztatowe
Material:	Aluminium/ Tworzywo sztuczne
Colour housing:	Czarny/Szary
Length/height [mm]:	61
Width [mm]:	56
Depth [mm]:	28
Weight total [g]:	80
The ports:	USB-C
Accessories:	Kabel ładowania
Additional information:	Ruchoma podstawka, magnes, gwint pod śrubę M6
Rechargeable:	tak
With light source:	tak