

Cable reel, PVC, H05VV-F 3x1.5mm² - 25m, 4 fixed sockets

Marka: Orno | Symbol: OR-AE-13291/25M | Ean: 5908254847066




PRODUCT DESCRIPTION

The cable reel enables to safely and reliably connect more devices to a single extension cord. It is equipped with 4 French-type sockets (2P+E) with safety shutters, which ensure convenience and compatibility with various electrical appliances.

Thanks to its durable construction made from high-quality plastic and a single thermal switch serving as overload protection, it ensures peace of mind and safety when connecting more appliances to one extension

socket. The PVC insulation guarantees durability and reliability of use.

The cable 25m long with H05VV-F 3x1,5mm² specification provides flexibility and freedom of use, without worrying about being too far from an outlet. The cable reel has current protection which guarantees smooth operation even while intensive use. The maximum load is 1100W/4,8A when the cable is coiled, and 3200W/13,9A when the cable is uncoiled.

The anti-twist system (fixed sockets) is an innovative feature designed to eliminate cable twisting during use, especially when four devices are connected at the same time.

A convenient handle for carrying as well as rotary drum winding handle provide ergonomics and comfort during transport.

The dimensions measure 247x341mm Black-dark blue colour.

TECHNICAL DATA

General information:

Material housing:	Tworzywo sztuczne
Cable assembly:	H05VV-F
Core cross section [mm²]:	1.5
Number of cores:	3
Number of sockets with protective contact (pin):	4
Cable length [m]:	25
With mounting frame:	Tak
With thermal protection:	Tak
With overload protection:	Tak
With adjustment:	Tak
Fixed sockets:	Tak
Protection:	Wyłącznik nadprądowy
Degree of protection (IP):	IP20
Colour:	czarno-granatowy
Supply voltage [V]:	230

Frequency [Hz]:	50
Current [A]:	16
Socket type:	2P+Z
Socket standard:	french (type E)
Number of network sockets:	4
Shutters for current paths:	Tak
Max. Load/current c cable rolled up:	1100W/4,8A
Max. Load/current cable unrolled:	3200W / 13,9A
Dimensions - width [mm]:	247
Dimensions - height [mm]:	341
Dimensions - depth [mm]:	204
Insulation type:	PVC