

Cable reel with 4 fixed socket IP44 30m, 4 socket 2P+E, rubber oil-resistant cord, H07RN-F 3x2.5mm², CUBE, thermal switch and safety shutters

ORNO

Marka: Orno | Symbol: OR-AE-13294/30M | Ean: 5908254847615



PRODUCT DESCRIPTION

The professional cable reel was designed for use in demanding indoor and outdoor conditions. The appliance is dedicated for professionals who need a reliable and safe source of power in any situation.

The product is equipped with 4 French-type sockets (2P+E) with safety shutters which additionally protect

against access to the sockets. The cable reel has an innovative anti-twist system, which prevents the cables from twisting while coiling and uncoiling.

The appliance is equipped with rubber, oil-resistant H07RN-F cable with a cross-section of 3x2,5mm² and length of 30m. It provides mechanical strength and resistance to oils and other chemical substances. This makes it perfect for use in harsh working conditions such as construction sites, workshops or garden works.

The built-in thermal switch protects the device against overload to ensure safe operation. If the maximum load is exceeded, the switch automatically cuts off the power supply, preventing damage to the cable and the connected equipment. The extension cord is designed to operate at a supply voltage of 230V and a frequency of 50Hz, with maximum load of 3200W (when the wire is uncoiled) or 1100W (when the wire is coiled).

Additionally, the sockets are equipped with covers that protect them against dirt, dust and moisture. This is particularly important in difficult environmental conditions. The covers are blue and characteristic for the top-quality products of Orno for Professionals brand. The IP44 rate ensures resistance against water splashing and dust. The device may therefore be used even in adverse weather conditions.

The cable reel is mounted on a metal CUBE stand, which provides stability and makes the cable reel easy to transport and use. The stand has a robust construction and an ergonomic rubber handle for increased carrying comfort. The product is also equipped with a drum rotation lock and a cable winding handle, making it much easier to use.

The dimensions of the cable reel measure 220x310x415 mm.

TECHNICAL DATA

General information:

Housing material:	Tworzywo sztuczne
Cable assembly:	H07RN-F
Core cross section [mm²]:	2.5
Number of cores:	3
Number of sockets with protective contact - pin (type E):	4
Cable length [m]:	30
With mounting frame:	Tak
Automatic cable winding:	Nie
With thermal overload protection:	Tak

With locking:	Tak
Protection:	Wyłącznik nadprądowy
Degree of protection (IP):	IP44
Colour:	czarno-granatowy
Fixed sockets:	Tak
Supply voltage [V]:	230
Frequency [Hz]:	50
Current [A]:	16
Socket type:	2P+Z
Socket standard:	french (typ E)
Number of network sockets:	4
Shutters for current paths:	Tak
Max. Load/current c cable rolled up:	1100W/4,8A
Max. Load/current cable unrolled:	3200W / 13,9A
Dimensions - width [mm]:	310
Dimensions - height [mm]:	415
Dimensions - depth [mm]:	220
Insulation type:	guma olejoodporna