

## Heavy-duty, splash-proof extension sockets, 3 Schuko sockets 2P+E, IP44, rubber cord, H05RR-F 3x1.5mm], 3m

ORNO

Marka: Orno | Symbol: OR-AE-13295(GS)/3M | Ean: 5908254847721



## PRODUCT DESCRIPTION

The splash-proof heavy-duty extension sockets is a solid and functional device designed for safe use in demanding conditions.

The unit is equipped with 3 Schuko-type mains sockets 2P+E which ensure save connection of three different devices and electrical appliances at the same time. It is designed to operate with a nominal voltage of 230V, 50Hz and a rated current of 16A and a maximum load of up to 3680W.



The sockets are equipped with safety shutters and protective covers, characteristic for the top-quality products of ORNO for PROFESSIONALS, which effectively protect against dirt and moisture. The IP44 rate means that the device may be used both indoors and outdoors.

**(1)** 

<u>에</u> ହ

The body is rectangular and made of solid plastic. It ensures durability and resistance to mechanical damage. The cable 3 m long has a cross-section of 3x1.5 mm<sup>1</sup> and H05RR-F insulation.

The device is equipped with a hook that allows to conveniently attach it in a safe place as well as holes for permanent installation at the workplace, increasing functionality and stability of the unit.

The dimensions measure 113x395x68 mm.

## **TECHNICAL DATA**

## General information:

Body shape:	Prostokątny
Number of sockets with protective contact (SCHUKO):	3
Socket type:	2P+Z
Standard socket:	Schuko (typ F)
Current path apertures:	Tak
With on/off switch:	Nie
Supply voltage [V]:	230
Frequency [Hz]:	50
Rated current [A]:	16
Max. load [W]:	3680
Number of conductors:	3
Cable cross section [mm]]:	1.5
Cable type:	H05RR-F
Insulation type:	guma
With lid:	Tak
Material:	Tworzywo sztuczne
Grade of material:	Tworzywo termoplastyczne



Surface protection:	Matowy
Color:	Czarny
Degree of protection (IP):	IP44
Power cord length [m]:	3
Angle-turned center insert:	Tak
Dimensions - width [mm]:	72
Dimensions - height [mm]:	285
Dimensions - depth [mm]:	53
Weight [kg]:	0.63