

Cable reel with 4 sockets, 30m, Schuko, PVC, H05VV-F 3x1.0mm² - 30m, 4x2P+E (Schuko), thermal switch

ORNO

Marka: Orno | Symbol: OR-AE-13300(GS)/30M | Ean: 5908254847431



PRODUCT DESCRIPTION

The cable reel allows more devices to be safely and reliably connected to a single extension socket. It has 4 Schuko type (2P+E) mains sockets with safety shutters, providing convenience and compatibility with a variety of electrical equipment.

Thanks to its robust construction in high-quality plastic and overload protection in the form of a single thermal circuit switch, it provides peace of mind and safety when connecting multiple devices to a single extension

socket. PVC type insulation guarantees durability and reliability of use.

The PVC cable with a 30m length and specification of H05VV-F 3x1mm² gives flexibility and freedom of use, without worrying about being too far from the socket. The device has current protection in the form of a thermal switch, which guarantees smooth operation even under intensive use. The maximum load is 900W/3.9A when the cable is coiled and 2300W/10A when the cable is uncoiled. Even the most demanding devices can be connected without hesitation.

Convenient carry handle and crank handle for cable retraction for ergonomics and comfort during transport. Dimensions are 247x341mm. Color black and navy blue.

TECHNICAL DATA

General information:

Housing material:	Tworzywo sztuczne
Cable assembly:	H05VV-F
Core cross section [mm ²]:	1
Number of cores:	3
Number of socket outlets with protective contact CEE 7/3 (type F):	4
Cable length [m]:	30
With mounting frame:	Tak
Automatic cable winding:	Nie
With thermal overload protection:	Tak
With locking:	Tak
Protection:	Wyłącznik nadprądowy
Degree of protection (IP):	IP20
Colour:	czarno-granatowy
Fixed sockets:	Tak
Supply voltage [V]:	230
Frequency [Hz]:	50
Current [A]:	10

Socket type:	2P+Z
Socket standard:	schuko (typ F)
Number of network sockets:	4
Shutters for current paths:	Tak
Max. Load/current c cable rolled up:	900W/3,9A
Max. Load/current cable unrolled:	2300W/10A
Dimensions - width [mm]:	225
Dimensions - height [mm]:	320
Dimensions - depth [mm]:	195
Insulation type:	PVC