

Wall socket 2P+Z with USB-A + USB-C charger, Schuko, 5VDC, 3A, white

ORNO

Marka: Orno | Symbol: OR-AE-13308(GS)/W | Ean: 5908254850387



PRODUCT DESCRIPTION

The modern single socket is a solution that combines the functionality of a traditional electrical socket with the possibility of connecting mobile devices thanks to a built-in USB charger.

The 2P+E socket in Schuko standard has been designed for mounting in a standard fi 60mm installation box. It operates with a supply voltage of 230V, 50Hz and a maximum load of 3680W.

The socket is equipped with two USB ports (A+C), for charging mobile devices, including phones, tablets, as well as Apple-branded devices such as the iPhone or iPad. The charger's maximum output power of 20W ensures fast and efficient charging.

The product is made of glass, which provides a modern and elegant look that will fit in with modern interiors. Dimensions: 87x87x10 mm. Available in white and black.

TECHNICAL DATA

General information:

| | |
|---|--|
| Model: | Gniazdo wtykowe CEE 7/3 (typ F) |
| Protective contact: | Blaszki uziemiające |
| Number of ports USB-A: | 1 |
| Number of ports USB-C: | 1 |
| Max. current rating of USB power supply [A]: | 3 |
| USB charger output parameters: | USB-C: 5V-3A, 9V-2.22A, 12V-1.67A USB-A: 5V-3A, 9V-2A, 12V-1.5A USB-C+USB-A: 5V-3.4A |
| Number of socket: | 1 |
| Number of phases: | 1 |
| Connection type: | Zacisk śrubowy |
| Safety shutters: | Tak |
| Label space/information surface: | Nie |
| Colour: | Biały |
| Mounting method: | Montaż podtynkowy |
| Type of fastening: | Montaż śrubowy |
| Material: | Szkło |
| Surface protection: | Stan surowy |
| Surface finishing: | Błyszczący |
| Nominal current [A]: | 16 |
| Nominal voltage [V]: | 230 |
| Max. load [W]: | 3680 |

| | |
|---|------|
| Frequency [Hz]: | 50 |
| Suitable for degree of protection (IP): | IP20 |
| Device width [mm]: | 87 |
| Device height [mm]: | 87 |
| Device depth [mm]: | 10 |
| Min. depth of built-in installation box [mm]: | 33 |