

ENTIKO DC, wireless battery-powered doorbell, learning system, 60 sounds, 300m, white

(1)

O R N O

Marka: ORNO Home | Symbol: OR-DB-RA-173/W | Ean: 5908254844959



PRODUCT DESCRIPTION

The wireless doorbell ENTIKO DC is a functional battery-operated device combined with new technologies. Designed for those who appreciate not only comfort of use but also the option of sound personalization.

The installation is simple and intuitive. Simply place the transmitter on a door or wicket, and the receiver in any place in the house. The receiver is powered by three AA batteries (not included). The transmitter is powered by one CR2032 battery - included in the set.



The range in the open field is 300m; thus, you may place the transmitter away from the house with no fear of losing the signal. What is more, the IP55 rate protects the transmitter from rain and dust ensuring reliability even in hard weather conditions.

<u>에</u> ହ

There is a wide range of ring tones to choose from to meet the user's expectations. ENTICO DC has as many as 60 available sounds and 5-stage volume control to adjust it to one' own preferences.

The built-in three signalling modes (visual-acoustic, visual, acoustic) facilitates to adjust the doorbell to the user's needs and the time of the day. The visual indication works well even when the ring tone is muted or turned off.

The aesthetic white colour of the transmitter and receiver makes the ringtone look elegant. Thanks to the learning system, the set may be expanded with additional transmitters, which makes it easily adaptable to one's own needs.

TECHNICAL DATA

General information:

Wireless:	tak
Max. transmission range [m]:	300
Frequency [MHz]:	433,92 MHz
Possibility of extension by an additional transmitters:	tak
Other features:	learning system

Receiver:

Type of current (receiver):	DC
Nominal voltage [V]:	4.5
Battery - type and quantity (receiver):	ЗхАА
Built-in battery (receiver):	nie
Electricity consumption [A]:	0.15
Number of ringtones:	60
Loudness [dB]:	92
Volume adjustment:	tak



Product data sheet

Volume adjustment range [dB]:	0-92
Optical indication:	tak
Mounting method:	Montaż natynkowy
Degree of protection (IP):	IP20
Housing material (receiver):	Tworzywo sztuczne
Colour housing:	Biały
Width (receiver) [mm]:	85
Height (receiver) [mm]:	85
Depth (receiver) [mm]:	33

Transmitter:

Type of current (transmitter):	DC
Nominal voltage (transmitter) [V]:	3
Battery - type and quantity (transmitter):	1xCR2032
Built-in battery (transmitter):	tak
Transmitter max. power [mW]:	10
Degree of protection (IP) (transmitter):	IP55
With lighting:	tak
With name plate:	tak
Housing material (transmitter):	Tworzywo sztuczne
Colour (transmitter):	Biały
Width (transmitter) [mm]:	30
Height (transmitter) [mm]:	56
Depth (transmitter) [mm]:	20