Symmetric electric strike with latch guide and lock, MINI, low current coil

Marka: **ORNO Home** | Symbol: **OR-EZ-4035** | Ean: **5908254804069**

PRODUCT DESCRIPTION

The smallest electric strike available on the market. It can work with the doorphones, video doorphones installation and code locks in the front of single- and multi-family doors It can be mounted on the outside of the standard faceplate Symmetrical design and small dimensions Made of corrosion resistant materials (aluminum and zinc alloy) Equipped with: safe, patented and adjustable latch keeper mechanism (2 mm). Electric strike has been equipped with Low current coil with wide voltage range , current consumption is 280mA for 12V direct current and 250mA for 12V alternating current.

ORNO GROUP Sp. z o. o. All rights reserved.

TECHNICAL DATA

General information:

Model:	Do drzwi standardowych
Type of latch:	Zatrzask standardowy
Construction type:	Symetryczny
Built-in position:	Pionowy
Height [mm]:	66
Width [mm]:	18
Depth [mm]:	28
Assembly arrangement:	Część ramowa (Elektro zaczep)
Voltage [V]:	10-24
With locking:	Tak
With Memory:	Nie
With latch regulation:	Tak
With feedback signal:	Nie
Opening direction according to DIN:	Lewy/prawy
Water protected:	Nie
Mounting method:	Do wbudowania
Type of current:	AC/DC
Principle of operation:	Prąd pracy
Unlocking method:	Model standardowy
Continuous operation (100 % ED):	Tak
Suitable for smoke protection door:	Tak
Utility category according to EN 14846:	3
Lasting functionability according to EN 14846:	C
Mass of door, clamp force according to EN 14846:	3
Suitable for fire- and smoke protection doors according to EN 14846:	A

ORNO GROUP Sp. z o. o. All rights reserved.

Safety - personal protection according to EN 14846:	0
Environmental condition according to EN 14846:	L
Safety - burglary protection according to EN 14846:	0
Protection effect electric operating mode according to EN 14846:	0
Protection effect mechanic operating mode according to EN 14846:	0
Connection voltage [V]:	10-24
Voltage type:	AC/DC
Power consumption during operation [mA/V DC]:	290/12

ORNO GROUP Sp. z o. o. All rights reserved.

ORNO GROUP Sp. z o. o. All rights reserved.