





## Floor box for module sockets 6 x 45x45mm or 12 x 22.5x45mm, cover: own material, black

Marka: Orno | Symbol: OR-GP-9202/CF | Ean: 5908254843167

ORNO



## PRODUCT DESCRIPTION

Floor box for module sockets was designed for indoor installations like offices or conference rooms. Its rectangular shape and grey color make it a perfect and functional fit in a variety of interiors.

The box is intended for six OR-GM-9010 modules freely modified to suit the user's preferences. There may be six 45x45 mm or twelve 22,5x45 mm modules placed in the box, or a combination of both.







The frame's height is regulated within the box. This facilitates precise adjustment of, e. g. straight and angle plugs inside the box, as well as facilitates the proper closing of the cover.

The product may be installed inside an access flooring. What is more, you may use a stainless steel OR-GP-9202MB box inside a concrete screed. This solution makes the box universe and durable in various conditions.

The minimum installation depth of 75 mm (adjustable within a range of 35 mm) makes the installation smooth and precise. The adjustment enables to level the socket with the floor.

The box was designed to protect cables and wires. It has one cable entry with protective foam that secures wires from damage. The product is fully safe as the cover of the socket may be closed even when in use.

The product has a cut-out for floor covering or other floor finish. You may place parquet, floor panel, stoneware, terracotta, floorboard or other material up to 8mm thick inside the cover. This makes the box adjustable to different types of flooring.

The housing is made of plastic. The socket may withstand a pressure of approximately 550N. The cover is made of steel.

After the cover is closed the ingress protection rate increases from IP20 to IP42. The box is suitable for dry cleaning.

## TECHNICAL DATA

## General information:

Cover model:	Prostokątny
Number of inlets:	6
Number of device cups:	6
With cable outlet in cover:	tak
Material housing:	Tworzywo sztuczne i stal
Surface protection housing:	Stan surowy
Material cover lid:	Stal
Cover load [kN]:	0.55
Degree of protection (IP):	IP20
With opening carpeting:	tak

Page 2 / 4









Depth of flooring recess [mm]:	8
Colour:	Szary
RAL-number:	7043
Suitable for indoor installation:	tak
Suitable for outdoor installation:	nie
Suitable for double floor built-in:	tak
Width outside dimension [mm]:	245
Length external dimension [mm]:	225
Length built-in dimension [mm]:	210
Width built-in dimension [mm]:	227
Min. built-in depth [mm]:	75

















