

## Floor box for module sockets 8 x 45x45mm or 16 x 22.5x45mm, cover: stainless steel, black

Marka: Orno | Symbol: OR-GP-9203/SS | Ean: 5908254843211



### PRODUCT DESCRIPTION

Floor box for module sockets was designed for indoor installations like offices or conference rooms. Its rectangular shape and grey color make it a perfect and functional fit in a variety of interiors.

The box is intended for eight OR-GM-9010 modules freely modified to suit the user's preferences. There may be eight 45x45 mm or sixteen 22,5x45 mm modules placed in the box, or a combination of both.

The frame's height is regulated within the box. This facilitates precise adjustment of, e. g. straight and angle plugs inside the box, as well as facilitates the proper closing of the cover.

The product may be installed inside an access flooring. What is more, you may use a stainless steel OR-GP-9203MB box inside a concrete screed. This solution makes the box universe and durable in various conditions.

The minimum installation depth of 75 mm (adjustable within a range of 35 mm) makes the installation smooth and precise. The adjustment enables to level the socket with the floor.

The box was designed to protect cables and wires. It has two cable entries with protective foam that secures wires from damage. The product is fully safe as the cover of the socket may be closed even when in use.

The housing is made of plastic additionally strengthened with a steel frame; therefore, the socket may withstand a pressure of approximately 550N. The cover is made of steel.

After the cover is closed the ingress protection rate increases from IP20 to IP42. The box is suitable for dry cleaning.

## TECHNICAL DATA

### General information:

<b>Cover model:</b>	Prostokątny
<b>Number of inlets:</b>	8
<b>Number of device cups:</b>	8
<b>With cable outlet in cover:</b>	tak
<b>Material housing:</b>	Tworzywo sztuczne i stal
<b>Surface protection housing:</b>	Stan surowy
<b>Material cover lid:</b>	Stal nierdzewna
<b>Cover load [kN]:</b>	0.55
<b>Degree of protection (IP):</b>	IP20
<b>With opening carpeting:</b>	nie
<b>Colour:</b>	Szary
<b>RAL-number:</b>	7043
<b>Suitable for indoor installation:</b>	tak

Suitable for outdoor installation:	nie
Suitable for double floor built-in:	tak
Width outside dimension [mm]:	328
Length external dimension [mm]:	230
Length built-in dimension [mm]:	215
Width built-in dimension [mm]:	310
Min. built-in depth [mm]:	75



