

Surface-mounted junction box HD IP68, 0.5-6.0mm², 2 glands M20, 2 glands M16, T-type

ORNO

Marka: Orno | Symbol: OR-JB-13815/4T | Ean: 5908254846519



PRODUCT DESCRIPTION

The surface-mounted Heavy-duty IP68 T-type junction box is a universal solution for protecting and connecting cables, perfect for indoor use in garages, houses, offices, as well as for outdoor use in gardens. The box facilitates to run cables and cover their connections in order to provide safety of use.

It is made of durable thermoplastic material (PC/PA66) which is known for its high resistance to UV radiation as well as to impacts (IK09). High ingress protection rate of IP68 guarantees full protection against dust as well

as against permanent submersion in water.

The black housing (RAL 9005) is equipped with two screw cable glands with a threat and M20 seal (2x 7-12 mm), which enable to run cable with 7 - 12 mm cross section, as well as two M16 glands (1x 5-10 mm).

Additionally, the box has 1x3 wire double-sided connector with a cross section of 0,75-4 mm² and 1x1 wire double-sided connector, which facilitates easy installation and ensures solid cable connections and a classic screw connector. The possibility of mounting it in the ground as well as its flame-retardant housing (UL94 V2 class) increase the universality of the product's application.

The box is rectangular and measures 82x69x39 mm.

TECHNICAL DATA

General information:

Assembly arrangement:	Puszka do montażu natynkowego
Shape:	Prostokąt
Material:	Tworzywo sztuczne
Material quality:	Tworzywo termoplastyczne
Type of material:	PC/PA66
Colour:	Czarny
RAL-number (similar):	9005
With screw gland entry:	Tak
Number of cable entries:	4
Type of scable entries:	2xM20; 2xM16
Size of cable entries:	2x(7-12mm); 2x(5-10mm)
Sealing Material:	Uszczelka silikonowa
Cap screws torque [N/m]:	0,5-2
Quick connector:	1x3-przewodowa, dwustronna, 1x1-przewodowa, dwustronna
Cross-section of quick-connector:	0,75-4mm ²
Underground installation::	Tak
Flame retardant housing:	Tak

Body fire rating UL94:	V2
UV-resistance:	Tak
Shock resistant:	IK09
Degree of protection:	IP68
Width of device [mm]:	82
Height of device [mm]:	69
Depth of device [mm]:	39





