

## Surface-mounted junction box HD IP68, 0.5-6.0mm<sup>2</sup>, 2 glands M20, 1 gland M16, X-type

**ORNO**

Marka: Orno | Symbol: OR-JB-13815/4X | Ean: 5908254846526



### PRODUCT DESCRIPTION

The surface-mounted Heavy-duty IP68 X-type junction box is a universal solution for protecting and connecting cables, perfect for indoor use in garages, houses, offices, as well as for outdoor use in gardens. The box facilitates to run cables and cover their connections in order to provide safety of use.

It is made of durable thermoplastic material (PC/PA66) which is known for its high resistance to UV radiation as well as to impacts (IK09). High ingress protection rate of IP68 guarantees full protection against dust as well

as against permanent submersion in water.

The black housing (RAL 9005) is equipped with two screw cable glands with a threat and M20 seal (2x 7-12 mm), which enable to run cable with 7 - 12 mm cross section, and two M16 glands (1x 5-10 mm).

Additionally, the box has 1x3 wire double-sided connector with a cross section of 0,75-4 mm<sup>2</sup> and 1x1 wire double-sided connector, which facilitates easy installation and ensures solid cable connections, and a classic screw connector. The possibility of mounting it in the ground as well as its flame-retardant housing (UL94 V2 class) increase the universality of the product's application.

The box is rectangular and measures 82x69x39 mm.

## TECHNICAL DATA

### General information:

<b>Assembly arrangement:</b>	Puszka do montażu natynkowego
<b>Shape:</b>	Prostokąt
<b>Material:</b>	Tworzywo sztuczne
<b>Material quality:</b>	Tworzywo termoplastyczne
<b>Type of material:</b>	PC/PA66
<b>Colour:</b>	Czarny
<b>RAL-number (similar):</b>	9005
<b>With screw gland entry:</b>	Tak
<b>Number of cable entries:</b>	4
<b>Type of scable entries:</b>	2xM20; 2xM16
<b>Size of cable entries:</b>	2x(7-12mm); 2x(5-10mm)
<b>Sealing Material:</b>	Uszczelka silikonowa
<b>Cap screws torque [N/m]:</b>	0,5-2
<b>Quick connector:</b>	1x3-przewodowa, dwustronna, 1x1-przewodowa, dwustronna
<b>Cross-section of quick-connector:</b>	0,75-4mm <sup>2</sup>
<b>Underground installation::</b>	Tak
<b>Flame retardant housing:</b>	Tak

Body fire rating UL94:	V2
UV-resistance:	Tak
Shock resistant:	IK09
Degree of protection:	IP68
Width of device [mm]:	82
Height of device [mm]:	69
Depth of device [mm]:	39





