

Power distribution block 125A, input terminal 1x16mm² and 1x35mm², output terminals 6x16mm².

Marka: Orno | Symbol: OR-LZ-8200/125 | Ean: 5908254809118

ORNO


PRODUCT DESCRIPTION

Power distribution blocks, suitable for DIN rail or mounting on a plate, help to connect heavy section cables. These blocks are used in electric switchboards and industrial casings for energy distribution.

TECHNICAL DATA

General information:

Type:	distribution block
Input screw terminals:	1x 6-16; 1x 10-35
Current:	125 A
Output terminals:	6x 2,5-16 mm ²
Installation:	DIN rail / mounting plate
Degree of protection (IP):	20
Insulation voltage Ui acc. to IEC:	1000 V
Insulation voltage Ui acc. to UL:	600 V
Rated short-time withstand current Icw:	4.2 kA
Peak short-circuit withstand current Ipk:	30 kA
Colour:	blue
Possibility of extension:	Yes
Compliance with standards:	IEC 60998-1, IEC 60998-2-1, IEC 60947-7-1, IEC 60947-7-1, UL 1059, UL 486E, CSA22.2 158-1987, GB 13140.1, GB 13140.2
Dimensions - depth:	77 mm
Dimensions - width:	29 mm
Mounting holes spacing:	64 mm
Dimensions - height:	46 mm
Screw tightening torque:	Input: 3,5 ; 8,5 Output: 3,5 Nm