

Power distribution block 80A, input terminal 16mm², output terminals 4x6mm², 2x16mm²

ORNO

Marka: Orno | Symbol: OR-LZ-8200/80 | Ean: 5908254809101



PRODUCT DESCRIPTION

Power distribution blocks, suitable for DIN rail or mounting on a plate, help to connect heavy section cables. These blocks are used in electric switchboards and industrial casings for energy distribution.

TECHNICAL DATA

General information:

Type:	distribution block
Input screw terminals:	1x 6-16
Current:	80 A
Output terminals:	4x 2,5-6; 2x 2,5-16 mm ²
Installation:	DIN rail / mounting plate
Degree of protection (IP):	20
Insulation voltage Ui acc. to IEC:	1000 V
Insulation voltage Ui acc. to UL:	600 V
Rated short-time withstand current Icw:	3 kA
Peak short-circuit withstand current Ipk:	22 kA
Colour:	blue
Possibility of extension:	Yes
Compliance with standards:	IEC 60998-1, IEC 60998-2-1, IEC 60947-7-1, IEC 60947-7-1, UL 1059, UL 486E, CSA22.2 158-1987, GB 13140.1, GB 13140.2
Dimensions - depth:	65 mm
Dimensions - width:	30 mm
Mounting holes spacing:	54 mm
Dimensions - height:	46 mm
Screw tightening torque:	Input: 3,5 Output: 1 ; 3,5 Nm