







AQUATIC PRO IP 55 doorbell button with illumination, grey/graphite

Marka: Orno | Symbol: OR-OE-7404/P/GR | Ean: 5908254829406

ORNO



PRODUCT DESCRIPTION

The Aquatic Pro, is a series designed for the most demanding users, characterised by a robust, sealed construction, a simple, universal design and a protection level for dust and spill resistance - IP55.

Internally, the Aquatic is fitted with rubber sealing elements, externally it is composed of solidly fitted components made of quality flexible plastic, which is resistant to impact and fading.







The Aquatic Pro doorbell button, is a surface-mounted button designed to operate a doorbell. It is a type of switch whose function is to activate a bell or chime every time it is pressed. In addition, this model is equipped with illumination - so it is ideal wherever the visibility of the button is important - in the corridor, at the wicket or outdoors.

The Aquatic Pro is also an aesthetically pleasing design that blends in with commercial interiors or industrial spaces. The series includes single-pole switches, two-button switches, single and double sockets, socket sets, doorbell buttons with and without illumination, and shutter switches.

The wide selection of elements makes it easy to complete a uniform furnishing for a room or even a building.

The series is in a grey-graphite colour scheme.

TECHNICAL DATA

General information:

Rated current [A]:	10
Width of device [mm]:	65
Height of device [mm]:	75
Depth of device [mm]:	55
Nominal voltage [V]:	230
Mounting method:	Montaż natynkowy
Assembly arrangement:	Element podstawowy z kompletną obudową
Method of operation:	Przycisk
Colour:	Szary
Model:	Przycisk pojedynczy
Connection type:	Wtykowe samozaciskowe
Imprint:	Brak
Surface protection:	Stan surowy
With signal lamp:	tak
Label space/information surface:	nie
Material quality:	Tworzywo termoplastyczne
Material:	Tworzywo sztuczne

Page 2 / 4

Update date: 2024-07-17 10:21:44











Type of fastening:	Mocowanie śrubowe
Number of rockers:	1
With lighting:	tak
Surface finishing:	Matowy
Suitable for degree of protection [IP]:	IP55
Number of contacts as normally open contact:	1
Quantity:	1















