

AQUATIC PRO IP55 Vertical Switch + Socket 2P+E, grey/graphite, 5pcs

Marka: Orno | Symbol: OR-OE-7407/GR/5 | Ean: 5908254830877

ORNO



PRODUCT DESCRIPTION

The Aquatic Pro, is a series designed for the most demanding users, characterised by a robust, sealed construction, a simple, universal design and a protection level for dust and spill resistance - IP55.

Internally, the Aquatic is fitted with rubber sealing elements, externally it is composed of solidly fitted components made of quality flexible plastic, which is resistant to impact and fading.

Consisting of a switch and an integrated 2P+E Aquatic Pro single socket, the Aquatic Pro is a module that allows you to easily complete the necessary fittings, even in large buildings. The socket-switch set is a basic set for every room.

The Aquatic Pro switch is a basic surface-mounted switch designed for connecting a single circuit to which, for example, a single lamp or a group of lamps can be connected.

Connected to the switch, the single 2P+E surface-mounted socket will provide safe access to the power supply - even if the room is not fully refurbished - the high level of dust and moisture resistance will allow you to use the fittings without worry.

The Aquatic Pro is also an aesthetically pleasing design that blends in with commercial interiors or industrial spaces. The series includes single-pole switches, two-button switches, single and double sockets, socket sets, doorbell buttons with and without illumination, and shutter switches.

The wide selection of components makes it easy to complete uniform equipment even for large installations.

The series is in a grey-graphite colour scheme. Package of 5 pcs.

TECHNICAL DATA

General information:

Nominal current [A]:	16
Frequency [Hz]:	50
Width of device [mm]:	65
Height of device [mm]:	150
Depth of device [mm]:	55
Nominal voltage [V]:	230
Mounting method:	Montaż natynkowy
Colour:	Szary
Model:	Ze stykiem ochronnym (bolec)
Number of units:	2
With hinged lid:	tak
Connection type:	Wtykowe samozaciskowe
Surface protection:	Stan surowy

With signal lamp:	nie
Number of phases:	1
With enhanced contact protection:	tak
With on/off switch:	tak
Protective contact:	tak
Label space/information surface:	nie
Material quality:	Tworzywo termoplastyczne
Insulated mounting:	tak
Material:	Tworzywo sztuczne
Type of fastening:	Montaż natynkowy
Surface finishing:	Matowy
Suitable for degree of protection [IP]:	IP55
Quantity:	5