

## AQUATIC PRO IP55 shutter switch, grey/graphite

Marka: Orno | Symbol: OR-OE-7408/GR | Ean: 5908254829451



### PRODUCT DESCRIPTION

The Aquatic Pro, is a series designed for the most demanding users, characterised by a robust, sealed construction, a simple, universal design and a protection level for dust and spill resistance - IP55.

Internally, the Aquatic is fitted with rubber sealing elements, externally it is composed of solidly fitted components made of quality flexible plastic, which is resistant to impact and fading.

The Aquatic Pro roller shutter switch is a surface-mounted switch intended for operating roller shutters or blinds, hence it is also commonly referred to as a shutter switch. This is a type of switch whose function is to activate the motor of the roller shutter mechanism, which allows it to be lowered or raised. The switch is equipped with two buttons (up and down) and a safety device to prevent them from being activated simultaneously.

The Aquatic Pro is also an aesthetically pleasing design that blends in with commercial interiors or industrial spaces. The series includes single-pole switches, two-button switches, single and double sockets, socket sets, doorbell buttons with and without illumination.

The wide selection of elements makes it easy to complete a uniform furnishing for a room or even a building.

The series is in a grey-graphite colour scheme.

## TECHNICAL DATA

### General information:

<b>Nominal voltage [V]:</b>	230
<b>Mounting method:</b>	Montaż natynkowy
<b>Assembly arrangement:</b>	Element podstawowy z kompletną obudową
<b>Method of operation:</b>	Przycisk wahadłowy
<b>Colour:</b>	Szary
<b>Model:</b>	Przycisk 2-biegunowy
<b>Connection type:</b>	Wtykowe samozaciskowe
<b>Surface protection:</b>	Stan surowy
<b>Rated current [A]:</b>	10
<b>Label space/information surface:</b>	Tworzywo termoplastyczne
<b>Material quality:</b>	Tworzywo termoplastyczne
<b>Number of poles:</b>	2
<b>Material:</b>	Tworzywo sztuczne
<b>Type of fastening:</b>	Montaż śrubowy
<b>Number of buttons:</b>	2
<b>Electrical and mechanical locking:</b>	tak

Surface finishing:	Matowy
Suitable for degree of protection [IP]:	IP55
Quantity:	1



