

Flush-mounted single-pole switch with illumination Luna, 10A, 250V, WP-1L/S, white

ORNO

Marka: Orno | Symbol: OR-OE-7600/P/W | Ean: 5904988912179



PRODUCT DESCRIPTION

Modular series of switches and mains sockets, IP20 rated, with a calm classic design. It has symmetrical frame plate system (for 1-, 2-, 3-, 4-, 5-modules) enabling to install the products both vertically and horizontally. The series includes the so-called middle frame, which guarantees proper mounting of the main frame or multiple frames to the wall. Additionally, it allows to create various colour options using frames, middle frames, buttons or socket covers, which is important in individual composition of the interior. The silver contacts of the switches are produced by welding, which guarantees much greater durability and security of the connection than in

the case of riveted contacts.

The switches' modern quick-connect mechanism (wires are connected by pushing them directly into the body) provides secure and safe wire installation and removal. The sockets are equipped with traditional screw connections. The internal design of the terminals guarantees secure connection of wires from 0.75 mm² to 2.5 mm². Strong and robust mounting plate grid and special mounting elements enable stable and secure installation in the box.

The single-pole switch with illumination is adapted to flush mounting. It is the simplest basic switch which operates on a single circuit and to which, for example, a single lamp can be connected. However, the product can also control other devices in the environment. In addition, this model is equipped with backlighting – so it will be perfect wherever the visibility of the button is important. It should be used indoors (IP20).

The product is available in white color. Dimensions 81x81x41mm.

TECHNICAL DATA

General information:

Wiring system:	Łącznik 1-biegunowy
Method of operation:	Przycisk wahadłowy
Assembly arrangement:	Element systemu modułowego do osprzętu elektroinstalacyjnego
Number of rockers:	1
Mounting method:	Montaż podtynkowy
Type of fastening:	Montaż pazurkowy / -śrubowy
Material:	Tworzywo sztuczne
Material quality:	Tworzywo termoplastyczne
Surface protection:	Malowanie
Surface finishing:	Błyszczący
Colour:	Biały
Label space/information surface:	Nie
Illumination:	Tak
Function lighting:	Orientacyjne
Suitable for degree of protection (IP):	IP20

Nominal voltage [V]:	250
Frequency [Hz]:	50
Rated current [A]:	10
Connection type:	Wtyk samozaciskowy
Device width [mm]:	81
Device height [mm]:	81
Device depth [mm]:	13
Built-in depth [mm]:	27
Min. depth of built-in installation box [mm]:	27



