

Flush-mounted two-button switch Luna, 10A, 250V, WP-2L, silver

Marka: Orno | Symbol: OR-OE-7601/G | Ean: 5904988912063

ORNO


PRODUCT DESCRIPTION

Modular series of switches and mains sockets, IP20 rated, with a calm classic design. It has symmetrical frame plate system (for 1-, 2-, 3-, 4-, 5-modules) enabling to install the products both vertically and horizontally. The series includes the so-called middle frame, which guarantees proper mounting of the main frame or multiple frames to the wall. Additionally, it allows to create various colour options using frames, middle frames, buttons or socket covers, which is important in individual composition of the interior. The silver contacts of the switches are produced by welding, which guarantees much greater durability and security of the connection than in

the case of riveted contacts.

The switches' modern quick-connect mechanism (wires are connected by pushing them directly into the body) provides secure and safe wire installation and removal. The sockets are equipped with traditional screw connections. The internal design of the terminals guarantees secure connection of wires from 0.75 mm² to 2.5 mm². Strong and robust mounting plate grid and special mounting elements enable stable and secure installation in the box.

The two-button switch is adapted to flush mounting. Product is used to control lighting, for example, composed of chandeliers and traditional or modern LED bulbs. It allows you to switch lighting on and off, divided into two or more zones. It should be used indoors (IP20).

The product is available in four colors: white, black, silver and black-gold. Dimensions 81x81x41mm.

TECHNICAL DATA

General information:

| | |
|--|--|
| Wiring system: | Łącznik 2-biegunowy |
| Method of operation: | Przycisk wahadłowy |
| Assembly arrangement: | Element systemu modułowego do osprzętu elektroinstalacyjnego |
| Number of rockers: | 2 |
| Mounting method: | Montaż podtynkowy |
| Type of fastening: | Montaż pazurkowy / -śrubowy |
| Material: | Tworzywo sztuczne |
| Material quality: | Tworzywo termoplastyczne |
| Surface protection: | Malowanie |
| Surface finishing: | Matowy |
| Colour: | Srebrny |
| Label space/information surface: | Nie |
| Suitable for degree of protection (IP): | IP20 |
| Nominal voltage [V]: | 250 |
| Frequency [Hz]: | 50 |

| | |
|---|--------------------|
| Rated current [A]: | 10 |
| Connection type: | Wtyk samozaciskowy |
| Device width [mm]: | 81 |
| Device height [mm]: | 81 |
| Device depth [mm]: | 13 |
| Built-in depth [mm]: | 27 |
| Min. depth of built-in installation box [mm]: | 27 |



