

Flush-mounted three-way switch Luna, 10A, 250V, WP-5L, silver

Marka: Orno | Symbol: OR-OE-7602/G | Ean: 5904988912100

ORNO


PRODUCT DESCRIPTION

Modular series of switches and mains sockets, IP20 rated, with a calm classic design. It has symmetrical frame plate system (for 1-, 2-, 3-, 4-, 5-modules) enabling to install the products both vertically and horizontally. The series includes the so-called middle frame, which guarantees proper mounting of the main frame or multiple frames to the wall. Additionally, it allows to create various colour options using frames, middle frames, buttons or socket covers, which is important in individual composition of the interior. The silver contacts of the switches are produced by welding, which guarantees much greater durability and security of the connection than in

the case of riveted contacts.

The switches' modern quick-connect mechanism (wires are connected by pushing them directly into the body) provides secure and safe wire installation and removal. The sockets are equipped with traditional screw connections. The internal design of the terminals guarantees secure connection of wires from 0.75 mm² to 2.5 mm². Strong and robust mounting plate grid and special mounting elements enable stable and secure installation in the box.

The three-way switch is adapted to flush mounting. Product is used to switch on and off the circuit to which the stair lighting is connected. This type of switches are always installed in pairs. The function of this type of switch is to activate, for example, lighting from different locations or floors. Similarly, the lighting in the bedroom, which you turn on when you enter the room and want to turn off right next to the bed, can be realized without going back to the main switch. It should be used indoors (IP20).

The product is available in four colors: white, black, silver and black-gold. Dimensions 81x81x41mm.

TECHNICAL DATA

General information:

Wiring system:	Łącznik schodowy
Method of operation:	Przycisk wahadłowy
Assembly arrangement:	Element systemu modułowego do osprzętu elektroinstalacyjnego
Number of rockers:	1
Mounting method:	Montaż podtynkowy
Type of fastening:	Montaż pazurkowy / -śrubowy
Material:	Tworzywo sztuczne
Material quality:	Tworzywo termoplastyczne
Surface protection:	Malowanie
Surface finishing:	Matowy
Colour:	Srebrny
Label space/information surface:	Nie
Suitable for degree of protection (IP):	IP20
Nominal voltage [V]:	250

Frequency [Hz]:	50
Rated current [A]:	10
Connection type:	Wtyk samozaciskowy
Device width [mm]:	81
Device height [mm]:	81
Device depth [mm]:	13
Built-in depth [mm]:	27
Min. depth of built-in installation box [mm]:	27



