

## Flush-mounted double socket 2x2P+E, Schuko Luna, 16A, 250V, PT-7L, white

**ORNO**

Marka: Orno | Symbol: OR-OE-7606(GS)/W | Ean: 5904988912346



### PRODUCT DESCRIPTION

Modular series of switches and mains sockets, IP20 rated, with a calm classic design. It has symmetrical frame plate system (for 1-, 2-, 3-, 4-, 5-modules) enabling to install the products both vertically and horizontally. The series includes the so-called middle frame, which guarantees proper mounting of the main frame or multiple frames to the wall. Additionally, it allows to create various colour options using frames, middle frames, buttons or socket covers, which is important in individual composition of the interior. The silver contacts of the switches are produced by welding, which guarantees much greater durability and security of the connection than in

the case of riveted contacts.

The switches' modern quick-connect mechanism (wires are connected by pushing them directly into the body) provides secure and safe wire installation and removal. The sockets are equipped with traditional screw connections. The internal design of the terminals guarantees secure connection of wires from 0.75 mm<sup>2</sup> to 2.5 mm<sup>2</sup>. Strong and robust mounting plate grid and special mounting elements enable stable and secure installation in the box.

Double Schuko-type socket, 2x2P+E. Designed for flush mounting in a frame plate system. It should be used indoors (IP20).

The product is available in two colors: white and silver. Dimensions 122x81x39.6mm.

## TECHNICAL DATA

### General information:

<b>Model:</b>	Gniazdo wtykowe CEE 7/3 (typ F)
<b>Protective contact:</b>	Blaszki uziemiające
<b>Number of units:</b>	2
<b>Number of modules (module system):</b>	1
<b>Number of phases:</b>	1
<b>Connection type:</b>	Zacisk śrubowy
<b>With enhanced contact protection:</b>	Nie
<b>Label space/information surface:</b>	Nie
<b>Colour:</b>	Biały
<b>Mounting method:</b>	Montaż podtynkowy
<b>Type of fastening:</b>	Montaż pazurkowy / -śrubowy
<b>Material:</b>	Tworzywo sztuczne
<b>Material quality:</b>	Tworzywo termoplastyczne
<b>Surface protection:</b>	Malowanie
<b>Surface finishing:</b>	Błyszczący
<b>Nominal current [A]:</b>	16
<b>Nominal voltage [V]:</b>	250

Frequency [Hz]:	50
Suitable for degree of protection (IP):	IP20
Device width [mm]:	122.5
Device height [mm]:	81.5
Device depth [mm]:	20
Min. depth of built-in installation box [mm]:	19